

IQConference Camera CV410



Specifications

Name	IQConference Camera
Model	CV410
Camera	
Image Sensor	1/2.5 Inch High Quality 4K CMOS Sensor
Effective Pixels	8.28MP, 16:9
Video Output	USB3.0, Type B.
Video Resolution	Main Stream : 3840×2160@30fps, 1920×1080P@30fps/25fps, 1280×720P@30fps/25fps Sub Stream : 1280×720P@30fps/25fps, 640×480P@30fps/25fps, 320×172P@30fps/25fps
View Angle	126° (D) /120°(H)/85°(V)
Focal Length	f=2.72mm
Iris	F2.5
Minimum Illumination	0.1Lux(F1.8, AGC ON)
Digital zoom	4X
DNR	2D&3D DNR
Super Low Illumination	On/off
White Balance	Auto / Manual/ One Push//3000K/3500K/4000K/4500K/5000K/5500K/6000K/6500K/7000K
Focus	Auto / Manual/ One Push
Super Low Illumination	On/off
Exposure	Auto / Manual
Backlight contrast	On/off
SNR	>55dB

USB Features	
Operation System	Windows 7(1080P/720P), Windows 8.1, Windows 10, macOS™ 10.10 and above, Linux (UVC)
Video Compression	YUY2, MJPG, H.264, H.265
USB Audio	Support
USB Protocol	UVC, UAC
PTZ Control	EPTZ
Hardware Request	2.4 GHz Intel® Core 2 Duo Processor or better, 2GB Catpcity or more , USB 2.0 Input(USB3.0 for 4K)
Other Specification	
Input Voltage	DC5V
Input Current	1A (Max.)
Power consumption	5W(Max.)
Store Temperature	-10°C ~ +60°C
Store Humidity	20% ~ 95%
Working Temperature	-10°C ~ +50°C
Working Humidity	20% ~ 80%
Dimension (WXHXD)	220mmX92.75mmX56mm
Application	Indoor
Accessory	User Manual, Warranty card, IR Controller

IQConference Camera CV410 (unit: mm)

