

Eaton EBAB32

Catalog Number: EBAB32

Eaton Basic Rack PDU, 0U, 36U, IEC-60309 input, 22 kW, 32A, 346-415V, Outlets: (24) C13/(6) C19

General specifications

Product Name	Catalog Number
Eaton basic rack PDU	EBAB32
Model Code	EAN
EPDU BA 0U (309 32A 3P)24XC13:6XC19	3553340696312
	Product Length/Depth
	1150 mm
Product Height	Product Width
52 mm	53 mm
Product Weight	Warranty
5.2 kg	2 year
Compliances	Certifications
CE Marked RoHS Compliant EAC	CE IEC 60950-1 EN 55024:2010
Model Code	
EPDU BA 0U (309 32A 3P)24XC13:6XC19	



Product specifications

Number of Outputs C13

24

Phase

Three-phase

Electrical connection

Connecting cord with plug

Mounting dimension (standardized)

Metric

Wattage

22 kW max

Form factor

0U (Vertical)

Mounting direction

Vertical

Amperage Rating

32 A

Package contents

Rack PDU

Mounting accessories

Quickstart guide

Safety Instructions

Input connection

IEC-60309 32A 3Ph

Fitted with:

Mounting material

Frequency rating

50/60 Hz

Operating Temperature

0° to 60°C (32° to 140°F)

Ethernet interface

No

Number of outlets with earth pin

30

Circuit breaker

(6) single-pole

Mass configuration

Resources

Application notes

[Eaton network closet solutions brochure](#)

[WUSD: Straight A's for K-12 virtualized environment](#)

[Application guide: Small data center power protection solutions](#)

[Eaton maintenance bypass application note](#)

Brochures

[Eaton ePDUs for office environments](#)

[Eaton ePDU G3 one-page overview](#)

[Eaton UPS Services Quick Guide 2021](#)

[Eaton ePDU G3 brochure](#)

[Eaton Flex and Hotswap MBP ePDU brochure](#)

[Eaton UPS and battery services](#)

[Eaton ePDU G3 - Brochure](#)

Case studies

[LACCD: Eaton solution proves knowledge is power for college district](#)

[Shawmigan Lake School: Boarding school protected by Eaton](#)

Certification reports

[Eaton RoHS declaration of conformity: ePDU G3](#)

Compliance information

[EU Declaration of Conformity Eaton ePDUs G3](#)

Drawings

[Eaton Basic ePDU visio stencils](#)

[EBAB32%20sk-106519-y1.pdf](#)

Installation instructions

[Eaton ePDU G3 troubleshooting guide](#)

User guides

[Eaton ePDU G3 1U and 2U installation addendum](#)

[Eaton ePDU G3 - Installation and Connectivity Quick Start](#)

[Eaton ePDU G3 operations manual](#)

[Eaton ePDU G3 installation and connectivity quick start](#)

[Eaton ePDU G3 replace and configure eNMC module](#)

White papers

[Optimizing rack power distribution](#)

[Quick guide to power distribution](#)

No

Special features

Built-in IEC outlet eGrip retention, retains all standard IEC plugs

Built-in outlet P-lock system, locking mechanism with P-lock power cords

60°C Operating temperature

Colour-coded outlet and branch circuits for simple load balancing

Hydraulic–Magnetic Circuit Breakers with accidental trip protection

Low-profile form factor: 52 mm wide x 53 mm deep on most models

Universal mounting system: Button mounting on rear and side + variable mounting system

Number of Outputs C19

6

Outlet control

No

Switchable

No

Cord length

3m

Input voltage

346-415V

Color

Black

SNMP

No

Material

Aluminium

Over voltage category

2

Outlets

(24) C13, (6) C19

Type

Rack PDU

Serial interface

No

Mounting Dimension (metrical)

52



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)