HP Premium Instant-dry Satin Photo Paper



hp

HP Premium Instant-dry Satin Photo Paper features unrivaled image quality. It provides an excellent versatility across a broad range of photo and displaygraphics applications.

- HP Premium Instant-dry Satin Photo Paper delivers image quality for brilliant photos and high-impact display graphics, posters, presentations and retail graphics, that make a big impression.
- HP Premium Instant-dry Satin Photo Paper dries instantly for immediate handling and lamination right off the printer saving time, streamlining workflows and increasing productivity.

 HP Premium Instant-dry Satin Photo Paper delivers exceptional results with both dye and fade-resistant UV inks, making it the ideal choice for photo and indoor display-graphics applications that demand unrivaled image quality.

Companies that produce trade show and event displays, posters and presentations. POP and retail displays, photo enlargements, art reproduction. Geographic Information Systems (GIS).



HP Premium Instant-dry Satin Photo Paper

Compatibility

HP Designjet printers	Ink Supplies	Front panel setting
HP Designjet 5500/5000 Printer series	HP 81 Dye & 83 UV Ink Supplies	HP Permium ID Satin

For the latest ICC/Media profiles, please visit www.hp.com/go/designjet/supplies/support (click on the ICC profiles and select your printer). For non-Post Script printers see your external RIP Vendor.

.3 mil/260 microns per ISC % per TAPPI T-452 Test Me 0 per CIE Ganz 82 Test Me 6, hot and cold. Visit HP's v tin to 30° C to 80% RH mination required 0 years (under glass) eater than 29 years (testing	ethod Method website for more information on lami	ination partners at: www.hp.com/go/designjet/supplies	
O per CIE Ganz 82 Test M s, hot and cold. Visit HP's v tin to 30° C to 80% RH nination required	Method website for more information on lami	ination partners at: www.hp.com/go/designjet/supplies	
to 30° C to 80% RH nination required vears (under glass)	website for more information on lami	ination partners at: www.hp.com/go/designjet/supplies	
to 30° C to 80% RH nination required Dyears (under glass)		ination partners at: www.hp.com/go/designjet/supplies	
to 30° C to 80% RH mination required Dyears (under glass)	g ongoing)		
to 80% RH nination required 9 years (under glass)	g ongoing)		
nination required P years (under glass)	g ongoing)		_
years (under glass)	g ongoing)		
	g ongoing)		
eater than 29 years (testing	g ongoing)		
s than 30 seconds (@ 23°	C, 50% RH)		
ears, unopened in origina	ıl packaging		
to 30° C			
to 65% RH			
rmany			
duct Numbers	Roll sizes	UPC codes	
994A	914 mm x 30.5 m	8 82780-08569 5	
996A	1067 mm x 30.5 m	8 82780-08571 8	
3000A	1524 mm x 30.5 m	8 82780-08575 6	
) ()	to 30° C to 65% RH rmany duct Numbers 994A 996A	to 65% RH rmany duct Numbers P94A P96A 1067 mm x 30.5 m 1000A 1524 mm x 30.5 m	to 30° C to 65% RH rmany duct Numbers Roll sizes UPC codes 294A 914 mm x 30.5 m 8 82780-08569 5 296A 1067 mm x 30.5 m 8 82780-08571 8

© Copyright 2005 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

