

## Key **Features**

Higher Brightness. Longer Lamp Life.

- Auto Power Off
- 22,000:1 contrast ratio
- SuperColor™ Technology
- 5 colour modes
- Vertical Keystone



## Product **Description**

The ViewSonic PA503S offers impressive visual performance in small business meeting rooms and classrooms. With higher brightness and longer lamp life, PA503S projector is guaranteed to reproduce the finest of details in any environment for much longer. ViewSonic exclusive SuperColour™ technology offers a wider range of displayable colour ensuring true-to-life colour accuracy in both bright and dark environments without sacrificing image quality.



08 09 10 11 1213

- 1. Keypad
- 2. LED indicator
- 3. Lamp cover
- 4. Security lock
- 5. Zoom/Focus
- 6. Front IR
- 7. Projection Lens
- 8. Audio in/out
- 9. HDMI
- 10. Dual VGA
- 11. VGA out 12. Mini USB
- 13. Video
- 14. Kensington® Lock Slot

15. RS232

**Visit Us** — www.viewsonic.com

SPECIFICATION		(
Native Resolution:	800x600	
DC type:	DC3	
Brightness:	3800 ANSI Lumens	
Contrast Ratio with SuperEco mode:	22000:1	
Display Colour:	1.07 Billion Colours	
Light Source:	Lamp	
Light source life (Nor/SuperEco):	5000/15000	
Lamp Watt:	190W	
Lens:	F=2.56-2.68, f=22-24.1 mm	
Projection Offset:	120%+/-5%	
Throw Ratio:	1.96~2.15	
Image size:	30" - 300"	
Throw Distance:	1.19m-13.11m(100" @3.98m)	9
Keystone:	±40° (Vertical)	
Optical Zoom:	1.1x	
Audible Noise (Eco):	27dB	
Resolution Support:	VGA(640 x 480) to FullHD(1920 x 1080)	
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p	
Video Compatibility:	NTSC, PAL, SECAM	
Horizontal Frequency:	15K~102KHz	
Vertical Scan Rate:	23~120Hz	
INPUT		
Computer in (D-SUB 15 pin):	2	
Composite:	1	
Audio-in (3.5mm):	1	
HDMI:	1 (Back)	
OUTPUT		
Monitor out (D-SUB 15 pin):	1	
Audio out (3.5mm):	1	
Speaker:	2W	
CONTROL		
RS232:	1	

USB type mini B (Services):

## **OTHERS**

Power Supply Voltage:	100-240V+/- 10%, 50/60Hz AC
Power Consumption:	Normal: 260W Standby: <0.5W
Operating Temperature:	0~40°C
Carton:	Brown
Net Weight:	2.2kg
Dimensions (WxDxH) w/adjustment foot:	294x218x110mm
Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S- Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese
STANDARD ACCESSORY	
Power Cord:	1
VGA cable:	1
Remote Control:	1
QSG & CD:	QSG: 1 / CD: NA
Air Filter:	RSPL