

Key **Features**

- 95% DCI-P3 & 100% sRGB wide color gamut coverage
- Hardware color calibration
- Delta E < 2 color accuracy
- · Pre-calibrated uniformity correction
- 21:9 aspect ratio



Product **Description**

With an immersive curved screen and stunning WQHD+ 3840x1600 resolution, the ViewSonic VP3881a monitor elevates your viewing experience from flat to panoramic. With Pantone validated 95% DCI-P3 & 100% sRGB color coverage, and an amazing Delta E<2 value, this 4K monitor provides industry standard color accuracy to ensure superior results, while HDR10 compatibility delivers a wider dynamic range of vivid colors and richer contrast. Thanks to an expansive 38″ frameless screen, ultra-wide 21:9 aspect ratio, and integrated speakers, this monitor is ideal for video editing, content development, and other color-critical applications. Featuring an incredible 60Hz refresh rate and AMD FreeSync™ technology, this monitor delivers smooth, tear-free playback ideal for video editors and game developers. With a sleek and modern design, the VP3881a features a future-proof USB-C port as well as DisplayPort technology, and HDMI. What's more, HDCP 2.2 content protection is standard across all ports to provide secure 4K content playback, streaming, and gaming. An integrated color uniformity function ensures consistent chromaticity across the screen, while a 14-bit 3D look-up table generates a stunningly smooth palette of 4.39 trillion colors. Hardware calibration is also available with the optional ViewSonic Colorbration Kit, which allows you to quickly and easily calibrate the monitor for photography, graphic design, and other professional applications.

Visit Us www.viewsonic.com

DISPLAY		CONTROLS	
Display Size (in.):	38	Physical Controls:	Key 1, Key 2, Key 3, Key 4, Key 5,
Viewable Area (in.):	37.5		Key 6 (power)
Panel Type:	IPS Technology	On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual
Resolution:	3840 x 1600	ODERATING COMPITIONS	Image Adjust, Setup Menu
Resolution Type:	WQHD+	OPERATING CONDITIONS Temperature:	32°F to 104°F (0°C to 40°C)
Static Contrast Ratio:	1,000:1 (typ)	Humidity (non-condensing):	20% to 90%
Dynamic Contrast Ratio:	20M:1	WALL MOUNT	20% 10 90%
Light Source:	LED	VESA Compatible:	100 x 100 mm
Brightness:	300 cd/m² (typ)	INPUT SIGNAL	100 X 100 IIIII
Colors:	1.07B	Frequency Horizontal:	15 ~ 135KHz
Color Space Support:	10 bit (8 bit + A-FRC)	Frequency Vertical:	24 ~ 75Hz
Aspect Ratio:	21:9	VIDEO INPUT	
Response Time (Typical GTG):	5ms		PCI-E - DisplayPort (v1.4), TMDS -
Response Time (GTG w/OD):	5ms	Digital Sync:	HDMI (v2.0), Micro-Packet - Type C
Viewing Angles:	178º horizontal, 178º vertical	ERGONOMICS	
Backlight Life (Hours):	30000 Hrs (Min)	Height Adjust (mm):	130
Curvature:	2300R	Swivel:	120°
Refresh Rate (Hz):	60	Tilt (Forward/Back):	-1° / 21°
Blue Light Filter:	Yes	WEIGHT (IMPERIAL)	
Flicker-Free:	Yes	Net (lbs):	27.7
Color Gamut:	Adobe RGB: 97% size / 86% coverage (Typ)DCI-P3: 96% size / 94% coverage (Typ)EBU: 129% size / 100% coverage (Typ)REC709: 131% size / 100% coverage (Typ)SMPTE-C: 441% size / 100% coverage (Typ)NSC: 92% size (Typ)SRGB: 131% size / 100% coverage (Typ)TSC: 92% size (Typ)SRGB:	Net Without Stand (lbs):	17.4
		Gross (lbs):	41.8
		WEIGHT (METRIC)	
		Net (kg):	12.6
		Net Without Stand (kg):	7.9
Pixel Size:	0.229 mm (H) x 0.229 mm (V)	Gross (kg):	18.9
Surface Treatment:	Anti-Glare, Hard Coating (3H)	DIMENSIONS (IMPERIAL) (W	XHXD)
COMPATIBILITY		Packaging (in.):	41.2 x 23.2 x 14.8
PC Resolution (max):	3840x1600	Physical (in.):	35.3 x 19.65~24.77 x 11.8
Mac® Resolution (max):	3840x1600	Physical Without Stand (in.):	35.3 x 15.7 x 4.1
PC Operating System:	Windows 7/8/8.1/10 certified; macOS	DIMENSIONS (METRIC) (WXI	
	tested	Packaging (mm):	1046 x 590 x 375
Mac® Resolution (min):	3840x1600	Physical (mm):	896 x 499.24~629.24 x 299
USB 3.2 Type A Down Stream:	2	Physical Without Stand (mm):	896 x 398 x 103
•	1	GENERAL	
USB 3.2 Type B Up Stream:	'	Regulations:	cTUVus, FCC-B, ICES003, Energy Star 8.0, EPEAT Bronze, CEC, NRCan, MX-CoC, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA, CCC, China RoHS, China
USB 3.2 Type C Up Stream; DisplayPort Alt mode :	1		
3.5mm Audio Out:	1		
HDMI 2.0 (with HDCP 2.2):	2		Energy Label
DisplayPort:	1		VP3881A x1, 3-pin Plug (IEC C13 / CEE22) x1, DisplayPort Cable (v1.2;
Power in:	External power adapter	PACKAGE CONTENTS:	Male-Male) x1, HDMI Cable (v2.0; Male-Male) x1, USB Type-C Cable (Male-Male) x1, USB A/B Cable
Ethernet LAN (RJ45):	1		
AUDIO			(v3.2; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1
Internal Speakers:	5Watts x2	Recycle/Disposal:	Please dispose of in accordance with
POWER			local, state or federal laws.
Eco Mode (Conserve):	36W	Warranty:	*Warranty offered may differ from market to market
Eco Mode (optimized):	41W	Power Management:	Energy Star standards, EPEAT
Consumption (typical):	52W		
Consumption (max):	56W		
Voltage:	AC 100-240V, 50/60 Hz		
Stand-by:	0.5W		
Power Supply:	External		
ADDITIONAL HARDWARE			
Kensington Lock Slot:	1		
Cable Organization:	Yes		