




## Key Features

- **OS-Free Architecture** minimizes vulnerabilities in secure and sensitive environments.
- **USB-C and HDMI 2.1** connectivity supports easy BYOD use without additional adapters.
- **Fast cold boot and 24/7 operation** ensures instant power-on and nonstop performance.
- **Built-in USB media playback** supports offline content delivery and digital signage.
- **ProAV system integration** enables centralized control.



## Product Description

The ViewSonic CDEG3-1C Series is an OS-free commercial display designed for secure, round-the-clock operation in mission-critical environments across corporate, government, healthcare, and higher education sectors. By eliminating pre-installed apps and background services, it reduces software attack surface while supporting fast boot times and simplified IT management. With native 4K UHD resolution in both landscape and portrait orientation, 500-nit brightness, and built-in USB media playback, this secure signage solution ensures clear visibility for announcements and digital displays in high-traffic environments. It also features extended connectivity options including USB-C, HDMI 2.1, LAN, and RS-232, making it well-suited for BYOD meetings and video conferencing. To further streamline remote device management, the commercial-grade display integrates with leading ProAV control systems. Certified EPEAT® Gold, CDEG3-1C Series digital displays offer a low-maintenance, sustainable solution that balances security, performance, and operational efficiency for any mission-critical space.



1. Control Panel

2. Speaker

3. LAN

4. SPDIF

5. Audio out

6. RS232 in

7. HDMI 3

8. HDMI 2

9. HDMI 1

10. Type C

11. VGA

12. Audio in

13. USB 2.0

14. USB 2.0

15. AC in

16. On/Off

17. VESA®/Wall Mount (600x400mm)

**Visit Us** [www.viewsonic.com](http://www.viewsonic.com)

**DISPLAY**

Panel Size:	65"
Type/ Tech:	TFT LCD module with DLED backlight
Display Area (mm):	1428.48 (H) x 803.52 (V) (64.5" diagonal)
Native Resolution:	3840 x 2160
Aspect Ratio:	16:9
Colors:	8bit+FRC
Brightness:	500 nits (typ.)
Contrast Ratio:	5000:1
Response Time:	6.5ms
Viewing Angles:	H = 178, V = 178 typ.
Backlight Life:	50,000 Hours
Surface Treatment:	Hardness: 3H, Anti-glare coating, Haze 25%
Bezel:	15.9/15.9/15.9/15.9 mm (L/R/T/B)
Orientation:	Landscape & Portrait

**REGULATIONS**

1. US NRTL with CA (TÜV SÜD)
2. FCC / ICES-003
3. Energy Star 8.0
4. EPEAT Gold
5. CE EMC
6. IEC68 CB
7. RoHS
8. ErP Directive
9. REACH SVHC List & DoC
10. Energy Efficiency Label
11. WEEE 12. SCIP
13. Annex I
14. Annex II
15. TPCH DoC
16. EU Packaging and Packaging Waste Directive
17. CA Prop 65 DoC
18. ISTA Certification

**PACKAGE CONTENTS**

1. 3 M power cord by ship area
2. Remote control
3. AAA battery x 2
4. Quick Start Guide
5. RS232 adapter
6. Clamp x 5
7. Screw x 4
8. HDMI cable 3 M (HDMI LA certified)
9. Compliance statement

**INPUT**

HDMI:	*3 (all support HDMI-CEC & HDCP1.4/2.2, HDMI 2.1 4K @ 60Hz, only HDMI 3 port support ARC) (Support YUV444/420)
RGB / VGA:	VGA IN *1 (1080p@60Hz)
Audio:	PC AUDIO IN *1 (3.5mm)
RS-232:	x 1

**OUTPUT**

Audio:	3.5mm x1
SPDIF:	x 1

**LAN**

RJ45:	x 1 (Support WOL)
-------	-------------------

**USB**

Type A:	*2 (for system update & media playback)
Type C:	*1 (with DP1.2/HDCP1.4/2.2 + Data2.0)

**SPEAKERS**

10W x 2
---------

**POWER**

Voltage:	100-240VAC +/- 10%
Consumption:	101.7W with Energy Star

**ERGONOMICS**

Wall Mount (VESA®):	600x400 mm
---------------------	------------

**OPERATING CONDITIONS**

Temperature (° C):	0 to 40°C (with Automatic Overheat Shutdown)
Humidity:	20% ~ 80% RH non-condensing

**OPERATING HOURS**

24/7
------

**DIMENSIONS (W X H X D)**

Physical (inch / mm):	1466.7 (W) x 841(H) x 79.7 mm(D) / 57.74 "(W) x 33.11 " (H) x 3.14 "(D)
-----------------------	---

**WEIGHT**

Net (lb / kg):	50.16 lb / 22.75 kg
Gross (lb / kg):	68.56 lb / 31.1kg