



Key Features

- Conquer every challenge with the silky-smooth 520Hz refresh rate
- Obliterate motion blur with the rapid 1ms (MPRT) response time
- Conquer stuttering and tearing with AMD FreeSync™ Premium and NVIDIA G-Sync compatible for smooth action
- Dual HDMI and DisplayPort inputs for flexible connectivity



Product Description

Dominate the competition with the ViewSonic GAMING XG2737 monitor, engineered to elevate your gaming performance. This powerhouse combines FHD resolution with a buttery-smooth 520Hz refresh rate, ensuring every frame is rendered with sharp, vivid clarity and outstanding fluidity. AMD FreeSync™ Premium and NVIDIA G-Sync compatible technology are integrated to eliminate motion blurring and screen tearing, presenting you with flawlessly smooth visuals that can keep pace with the intensity of your gameplay. Prepare to experience every scene with cinematic detail and feel the rush of adrenaline as you become one with the action.



Visit Us www.viewsonic.com

DISPLAY

Display Size (in.):	27
Viewable Area (in.):	27
Panel Type:	IPS Technology
Resolution:	1920 x 1080
Resolution Type:	FHD (Full HD)
Static Contrast Ratio:	1,000:1 (typ)
Dynamic Contrast Ratio:	80M:1
High Dynamic Range:	HDR10
Light Source:	LED
Brightness:	400 cd/m² (typ)
Colors:	16.7M
Color Space Support:	8 bit (6 bit + FRC)
Aspect Ratio:	16:9
Response Time (Typical GTG):	1ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	Flat
Refresh Rate (Hz):	520
Variable Refresh Rate Technology:	FreeSync Premium, G-Sync compatible
Low Blue Light:	Software solution
Flicker-Free:	Yes

Color Gamut: NTSC: 89% size (Typ)
sRGB: 125% size / 99% coverage (Typ)

Pixel Size: 0.311 mm (H) x 0.311 mm (V)
Surface Treatment: Anti-Glare, Hard Coating (3H)

COMPATIBILITY

PC Resolution (max):	1920x1080
Mac® Resolution (max):	1920x1080
PC Operating System:	Windows 10/11 certified; macOS tested
Mac® Resolution (min):	1920x1080

CONNECTOR

USB 3.2 Type A Down Stream:	2
USB 3.2 Type B Up Stream:	1
3.5mm Audio Out:	1
HDMI 2.1:	2
DisplayPort:	1
Power in:	3-pin Socket (IEC C14 / CEE22)

AUDIO

Internal Speakers:	2Watts x2
--------------------	-----------

POWER

Eco Mode (Conserve):	34W
Eco Mode (optimized):	39W
Consumption (typical):	43W
Consumption (max):	62W
Voltage:	AC 100-240V
Stand-by:	0.5W
Power Supply:	Internal Power Supply

ADDITIONAL HARDWARE

Kensington Lock Slot:	1
Cable Organization:	Yes

CONTROLS

Physical Controls:	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu

OPERATING CONDITIONS

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity (non-condensing):	20% to 90%

WALL MOUNT

VESA Compatible:	100 x 100 mm
------------------	--------------

INPUT SIGNAL

Frequency Horizontal:	30 ~ 600KHz
Frequency Vertical:	48 ~ 520Hz

VIDEO INPUT

Digital Sync:	FRL - HDMI (v2.1), HBR3 - DisplayPort (v1.4)
---------------	--

ERGONOMICS

Height Adjust (mm):	130
Swivel:	90°
Tilt (Forward/Back):	-5° / 20°

WEIGHT (IMPERIAL)

Net (lbs):	16.4
Net Without Stand (lbs):	11.8
Gross (lbs):	21.6

WEIGHT (METRIC)

Net (kg):	7.5
Net Without Stand (kg):	5.4
Gross (kg):	9.8

DIMENSIONS (IMPERIAL) (WXHxD)

Packaging (in.):	26.9 x 17.5 x 8.2
Physical (in.):	24.17 x 15.19~20.31 x 7.48
Physical Without Stand (in.):	24.17 x 14.43 x 2.07

DIMENSIONS (METRIC) (WXHxD)

Packaging (mm):	682 x 445 x 208
Physical (mm):	613.8 x 385.8~515.8 x 190
Physical Without Stand (mm):	613.8 x 366.4 x 52.5

GENERAL

Regulations:	CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, BIS
PACKAGE CONTENTS:	XG2737 x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v2.1; Male-Male) x1, DisplayPort Cable (v1.4; Male-Male) x1, Quick Start Guide x1
Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
Warranty:	*Warranty offered may differ from market to market