

LCD 65" Message Large Format Display

# Sharp MultiSync® M652



## Built to perform, designed to last

The versatile solution for professional display applications, the Sharp MultiSync® M2 Series (32" up to 98") is purpose-built for demanding signage and meeting room environments. With native USB-C connectivity and broad compatibility with platforms such as Crestron, Cisco Webex, and Microsoft Teams, it enables seamless BYOD collaboration and future-ready integration, while 802.1x LAN support ensures enterprise-grade network security. Featuring class-leading 550 cd/m<sup>2</sup> brightness, a high-haze panel to minimise glare, and NEC's trusted SpectraView Engine, the M2 Series delivers outstanding visual performance with unmatched colour precision.

As part of the new Sharp-branded display family, the MultiSync® M2 Series builds on NEC's legacy of quality and reliability to drive greater efficiency and long-term value. Its proven modular design supports custom computing options (Raspberry Pi or Intel® SDM) and flexible connectivity (e.g. AV-over-IP), ensuring lasting versatility, performance, and sustainability.

## Benefits

**Seamless meeting workflows** – a single USB-C cable transmits video, data, and power for instant, clutter-free meeting setups. As the established standard for modern collaboration spaces, USB-C supports frictionless BYOD experiences.

**Unhindered readability** – a high-haze panel reduces glare from windows and ambient light, keeping signage content and presentations clear for uninterrupted viewing in any environment

**Security assured** – 802.1x support over LAN enables high-level security for corporate networks, giving peace of mind for IT teams and enterprise environments.

**Enhanced imaging precision** – when brand consistency and corporate identity are important, NEC's SpectraView Engine provides full control over colour, gamma, and uniformity for accurate and impactful content.

**Broad AV compatibility** – fully interoperable with leading meeting room platforms including Crestron (XiO Cloud), Cisco Webex, Q-Sys, and Microsoft Teams, ensuring effortless integration and future-proof scalability.

# Specifications

## Product Information

### Product Name

Sharp MultiSync® M652

### Model

PN-M652

### Product Group

LCD 65" Message Large Format Display

### Order Code

PNM652

## Display

### Panel Technology

IPS with Direct LED backlights

### Active Screen Area (W x H) [mm]

1,428.5 x 803.5

### Screen Size [inch/cm]

65 / 163.9

### Aspect Ratio

16:9

### Pixel Pitch [mm]

0.372

### Brightness [cd/m<sup>2</sup>]

550

### Contrast Ratio

≥ 8000:1<sup>1</sup>

### Viewing Angle [°]

178 horizontal / 178 vertical (typ. at contrast ratio 10:1)

### Colour Depth [bn]

1.073 (10bit)

### Colour Gamut

72% of NTSC

### Response Time (typ.) [ms]

8

### Panel Refresh Rate [Hz]

60

### Haze Level [%]

Pro (25)

## Supported Orientation

Face Up<sup>2</sup>; Landscape; Portrait

## Resolution

### Native Resolution

3840 x 2160

### Supported Resolutions

1024 x 768;	1440 x 900;	4096 x 2160;
1270 x 720;	1600 x 1200;	640 x 480;
1280 x 1024;	1680 x 1050;	720 x 400;
1280 x 720;	1920 x 1080;	720 x 480;
1280 x 800;	1920 x 1200;	720 x 576;
1360 x 768;	1920 x 1200;	800 x 600
1366 x 768;	1920 x 2160;	
1400 x 1050;	3840 x 2160;	

## Synchronisation Rate

### Horizontal Frequency [kHz]

15 - 135

### Vertical Frequency [Hz]

23 - 76

## Connectivity

### HDMI IN 1

Video Input; UHD (60 Hz) HDCP (2.2); Audio Input; ARC; CEC

### HDMI IN 2

Video Input; UHD (60 Hz) HDCP (2.2); Audio Input; CEC

### HDMI OUT

Video Output; UHD (60 Hz) HDCP (2.2); Audio Output; Loop Through: HDMI IN 2, Option, Compute module

### DP IN 1

Video Input; UHD (60 Hz) DP 1.2; HDCP (2.2); Audio Input

### DP OUT

Video Output; UHD (60 Hz) DP 1.2; HDCP (2.2); Audio Output; Loop Through: DisplayPort IN, USB-C 2

### USB-A 1

USB (2.0 / 3.2); 4.5 W; Peripherals; USB Storage

### USB-A (Service)

2.5 W; Service

### USB-C 1

Video Input; UHD (60 Hz); DP alt. 1.2; HDCP (2.2); Audio Input; USB 2.0 / 3.2; 65 W

---

### USB-C 2

USB 2.0 / 3.2; 7.5 W; Peripherals; Storage

---

### Audio Output (3.5 mm)

Audio Output; Line Out

---

### LAN 1

100 MBit/s

---

### LAN 2

Loop Through: LAN 1, RS-232C, IR; 100 MBit/s

---

### RS-232C

9600 bps

---

### Remote In (3.5 mm)

Eco Sensor (IR-Extender, Ambient and Presence)

---

### Input Detect

Custom; Last; First

---

### PiP / PbP

2-Split; Scalable picture size

---

## Calibration

### Factory Calibration

Gamma; Intensity; RGB; Uniformity; White Point

---

### Calibration with Software

Corner Uniformity; Gamma; Intensity; RGB; Update Factory Calibration; White Point

---

### Calibration Software

Display Wall Calibrator

---

## Open Modular Intelligence

### Intel® SDM

accepts Intel® Smart Display Modules Large and Small up to 66 W

---

### Compute Module Slot

MPI4 and MPI5 Kit (powered by Raspberry Pi)

---

## Sensors

### Ambient Light Sensor

Integrated, triggered actions programmable

---

### Human Sensor

optional via Eco Sensor (KTES1)

---

### Temperature Sensor

Integrated, 3 sensors, triggered actions programmable

---

## Electrical

### Power Consumption [W]

135 shipping

---

### Power Savings Mode [W]

< 0.5; < 2 (Networked Standby)

---

### Power Management

VESA DPMS

---

### Power Supply

100-240 V AC; 50/60 Hz; internal

---

## Environmental Conditions

### Operating Temperature [°C]

+0 to +40

---

### Operating Humidity [%]

20 to 80

---

### Storage Humidity [%]

10 to 80

---

### Storage Temperature [°C]

-20 to 60

---

## Mechanical

### Dimensions (W x H x D) [mm]

1,454.5 x 832.4 x 59.5

---

### Weight [kg]

26

---

### Bezel Width [mm]

11 (left/right/top); 13.9 (bottom)

---

### VESA Mounting [mm]

4 holes; 400 x 400 (FDMI); M6

---

### Ingress Protection

IP5x (front); IP2x (back)

---

### Packaging Dimensions (W x H x D) [mm]

1,620 x 950 x 185

---

### Packaging Weight [kg]

35

---

### Material

Metal

---

## Available Options

### Accessories

Eco Sensor (KTES1); Feet (ST-65M); Remote control kit (KTRC3); Soundbar (PN-ZCMS1); Speaker (SP-RM3a); Trolley (PD04 Tipster, L20PNSR780MEU); USB-C cable (USB-C 5M, USB-C 7M); Wall mount (PDW S 32-65 L, PDW S 32-65 P, L20PNWALL90EU, PDW T XL-2)

## Regulatory

### Safety and Ergonomics

CE; EMC Class B; Energy Star 8; FCC Class B; REACH; RoHS; UKCA; UL/C-UL or CSA

### Pixel Failure Class

ISO 9241-307, Class 1

### Resistance to Fire

Metal backcover, plastic material certified acc. to UL94-5VB

## Green Features

### Energy Efficiency

Energy consumption: 130 kWh/1000 h; Energy efficiency class: G; LED backlight

### Ecological Standards

EnergyStar 8.0

## 3rd Party Certifications

### Crestron

Certified for Crestron CCV2 and XiO Cloud

## Additional Features

### Special Characteristics

CEC Support; Clone Settings; DICOM Simulation; HDMI ARC; Scheduler

### Colour Versions

Black Front Bezel, Black Back Cabinet

### Audio

Integrated Speakers (10 W + 10 W)

### Shipping Content

2x AAA batteries; Display; HDMI Cable; Power Cable; Remote Control; Setup Manual

### Warranty

3 years warranty incl. backlight; additional services available; optional 4. + 5. year warranty extension<sup>3</sup>

### Operating Hours

24/7

### External Control

AMX NetLinx Support; Crestron V2; HDMI CEC; HTTP Browser; PJLink; Scheduled Timer; SNMP

### Remote Management

NaViSet Administrator 2

### Security

Disable HW Buttons; Disable IR Functionality; IEEE802.1X (LAN)

<sup>1</sup> out of the box conditions, local dimming ON

<sup>2</sup> adjusted usage conditions for face up/down installations, please refer to operational guidelines or contact our support

<sup>3</sup> please refer to terms and conditions of warranty extensions



RoHS



FCC Class B



CE

This document is © 2026 Sharp Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 20.05.2026