

Key Features

- 1.21-1.57 throw ratio enables seamless projector upgrades
- 4,000 ANSI Lumens offering bright images in any environment
- Convenient connectivity with dual HDMI and USB-A power supply
- Comprehensive LAN control for centralized device management
- High native contrast ratio
 achieved through Texas
 Instruments' 0.65" DMD chip



Product **Description**

The ViewSonic PA504W is a high-brightness lamp projector tailored for both education and business settings. It features a 1.21-1.57 throw ratio, allowing seamless projector upgrades in typical installation conditions. With 4000 ANSI Lumens, it ensures bright, vivid images even in well-lit environments, guaranteeing clarity for every presentation or lesson. Its Texas Instruments' 0.65" DMD Chip elevates the viewing experience with a high native contrast ratio, unveiling fine details for exceptional sharpness on the screen. Effortlessly switch between content sources via the dual HDMI ports. Additionally, you can combine it with the ViewSonic WPD-700 Wireless Screen Casting Kit, powered by the projector's USB-A output, for expanded versatility. Comprehensive LAN control takes this convenience further, providing streamlined device management. Based on DLP technology, it maintains consistent color performance and great readability over time and features a filter-free design for minimal maintenance requirements.





- 1. Adjustment Foot
- 2. Lens
- 3. Front IR
- 4. Audio In
- 5. HDMI x2 6. USB-A(5V/1.5A, Service) 7. Computer In
- 8. Monitor Out
- 9. Video In
- 10. RJ45

- 11. Audio Out 12. AC In 13. RS232 14. Kensington Lock
- 15. Zoom/Focus Ring
- 16. Keypad 17. LED Indicator
- 18. Power Button

Visit Us www.viewsonic.com



SPECIFICATION

OTHERS

		· · · · · · · ·	
Native Resolution: Brightness:	1280x800 4000 (ANSI Lumens)	Power Supply Voltage:	100-240V+/- 10%, 50/60Hz (AC in)
Contrast Ratio with SuperEco Mode:	22000:1	Power Consumption:	Normal: 255W Standby: <0.5W
Display Color:	1.07 Billion Colors	Operating Temperature:	0~40°C
Light Source Type:	200W UHP Lamp	Carton:	Brown
Light Source Life (hours) with	5000	Net Weight:	2.33kg
Normal Mode:		Gross Weight:	3.54kg
Light Source Life (hours) with SuperEco Mode:	15000	Dimensions (WxDxH) with Adjustment Foot:	294x218x110mm
Lens:	F=2.59-2.87, f=16.88- 21.88mm	Packing Dimensions:	415x168x297mm
Projection Offset:	120%+/-5%		English, French,
Throw Ratio:	1.21-1.57	OSD Language:	Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese, Greek, Total 23 languages
Optical Zoom:	1.3x		
Digital Zoom:	0.8x-2.0x		
Image Size:	30"-300"		
Throw Distance:	0.78m-10.14m (100"@2.61m)		
Keystone:	V:+/-40°		English, S-Chinese, T-
Audible Noise (Normal):	31dB	User Guide Language:	Chinese, Indonesian, Finish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Czech, Thai, Vietnamese, Total 20
Audible Noise (Eco):	27dB		
Input Lag:	16ms		
Resolution Support:	VGA(640 x 480) to FullHD(1920 x 1080)		
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p	STANDARD ACCESSORY	languages
Video Compatibility:	NTSC, PAL, SECAM	Power Cord:	1
Horizontal Frequency:	15K-102KHz	VGA Cable:	1
Vertical Scan Rate:	23-120Hz	Remote Control:	1
INPUT		QSG:	Yes
Computer in (share with component):	1	Warranty Card:	Yes (CN only)
Composite:	1	OPTIONAL ACCESSORY	
	2	Lamp/Light Source:	RLC-130
HDMI:	(HDMI 1.4/ HDCP 1.4)	Wall/Ceiling Mount:	PJ-WMK-007
Audio-in (3.5mm):	1	Carry Bag:	PJ-CASE-008
OUTPUT			
Monitor out:	1		
Audio-out (3.5mm):	1		
Speaker:	10W		
USB Type A (Power):	1 (5V/1.5A)		
CONTROL			
RS232 (DB 9-pin male):	1		
RJ45 (LAN control):	1		
USB Type A (Services):	1 (share with USB A Output)		



Copyright © ViewSonic Corporation 2000-2024. All rights reserved.

