

PF-Series LED-backlit Display 55"

High Brightness Free Standing Kiosk



Built on a MVA panel with 700-nit high brightness capability and a 4000:1 contrast ratio, the PF-Series ensures lifelike images even in settings with strong ambient lighting. Equipped with varied connections and built-in speakers, the series easily integrates with IPC or media player for versatile media playback. With tempered glass on the front, and a metal housing and movable floor stand, the PF-55H is ideal for public environments.





Reliability and Durability

Tempered glass on the front that stretches from top to base, a strong metal casing, and a safe and secure locking back cover makes the display suitable for public settings while ensuring data protection.

Easy to Connect and Move

The PF-Series offers USB, VGA, HDMI and DVI connections and also a storage area for media players/ IPCs. Its free-standing and movable floor stand makes the display of content convenient in a variety of locations.

* USB port for IPC remote control extension only



High Visibility

With a brightness level that reaches 700 nits and a VA technology panel that provides a wide viewing angle, the PF-55H is able to meet the visual requirements for semi-outdoor use.

Features

- Full HD 1920 x 1080 resolution
- 700 nits high brightness panel offers clear images in bright ambient light areas
- VA Panel technology ensures accurate colours and offers high contrast ratios with wide viewing angles
- Front-sided tempered glass protection from top to base
- Durable metal housing
- Glossy piano black front bezel and matte black back design
- Built-in USB media player for simple signage content delivery
- Safe and secure locking back cover
- Built-in speakers
- Free standing and movable floor stand



Specifications

PF-55H

Panel	Panel Type	LED-Backlit TFT LCD (VA Technology)
	Panel Size	54.6"
	Max. Resolution	FHD 1920 x 1080
	Pixel Pitch	0.630 mm
	Brightness	700 cd/m ²
	Contrast Ratio	4000:1
	Viewing Angle (H/V)	178°/178°
	Display Colour	1.07B
	Response Time	5 ms
	Surface Treatment	Anti-Glare Treatment (Haze 11%), 3H Hard Coating
Frequency (H/V)	H Freq.	10 kHz-88 kHz
	V Freq.	10 Hz-93 Hz
Input	HDMI	1.2 x 1
	DVI	24-Pin DVI-D x 1
	VGA	15-Pin D-Sub x 1
Other Connectivity	USB	2.0 x 1 (Service Port)
Audio	Audio In	Stereo Audio Jack (3.5 mm)
	Audio Out	Stereo Audio Jack (3.5 mm)
	Internal Speakers	10W x 2
Power	Power Supply	Internal
	Power Requirements	AC 100-240V, 50/60 Hz
	On Mode	170W (On)
	Stand-by Mode	< 1.0W
Glass	Thickness	5.0 mm (0.20")
	Hardness	> 9H
Operating Conditions	Temperature	0°C-40°C (32°F-104°F)
	Humidity	20%-80% (non-condensing)
Storage Conditions	Temperature	-10°C-50°C (14°F-122°F)
	Humidity	20%-80% (non-condensing)
Dimensions	w/Base (W x H x D)	815.0 x 1975.0 x 651.0 mm (32.1" x 77.8" x 25.6")
	Packaging (W x H x D)	2050.0 x 930.0 x 770.0 mm (80.7" x 36.6" x 30.3")
Weight	w/Base	105.0 kg (231.0 lb)
	Packaging	115.0 kg (253.0 lb)
Regulation Approval	Certifications & Compliance	CE, LVD, RoHS, WEEE, REACH
Accessories	Supplied	Power Cord, DVI Cable, User Manual (printed)

Global Headquarters

Taipei, Taiwan

EMEA Regional Headquarters

Capelle a/d IJssel, The Netherlands

North & South America Regional Headquarters

San Jose, CA, U.S.A.

Asia-Pacific Regional Headquarters

Taipei, Taiwan

Canada Sales Office

Vancouver, B.C., Canada

China Sales Office

Shanghai, China

Czech Republic Sales Office

Brno, Czech Republic

Denmark Sales Office

Støvring, Denmark

Germany Sales Office

Mechernich, Germany

Italy Sales Office

Livorno, Italy

Poland Sales Office

Warsaw, Poland

Spain Sales Office

Barcelona, Spain

Ukraine Sales Office

Lviv, Ukraine

displays.agneovo.com