

Key Features

- **Lifelike True Beauty:** International colour standard Pantone validated and 100% sRGB wide colour gamut
- **Precise Colour:** ColorPro Verified with pre-factory calibration for overwhelmed Delta E < 2 colour accuracy
- **Multimedia Devices:** Support USB-C with 60W high-speed charging, plus HDMI 2.0, DisplayPort 1.4, USB3.2
- **Unlimited Flexibility:** Auto Pivot & Ergonomic Stand with tilt, swivel, pivot, and height adjustments
- **The Visible Difference:** 4K UHD(3840* 2160) resolution IPS panel with 32" frameless design



Product Description

Designed with creative professionals in mind, the ViewSonic VP3256-4K delivers stunning true-to-life colours on screen. Pantone validated 100% sRGB coverage provides precise colour reproduction, ensuring your work looks how it should, every time. A USB-C port that easily connects with your devices for easy charging and data transfer. Ergonomic engineering gives you the flexibility to do more without injury, while Auto Pivot lets shift between horizontal and vertical orientations effortlessly, letting your work be viewed how it's supposed to be.

Visit Us — www.viewsonic.com

DISPLAY		OPERATING CONDITIONS	
Display Size (in.):	32	Temperature:	32°F to 104°F (0°C to 40°C)
Viewable Area (in.):	31.5	Humidity (non-condensing):	20% to 90%
Panel Type:		WALL MOUNT	
Resolution:	3840 x 2160	VESA Compatible:	100 x 100 mm
Resolution Type:		INPUT SIGNAL	
Static Contrast Ratio:	1,000:1 (typ)	Frequency Horizontal:	15 ~ 136KHz
Dynamic Contrast Ratio:	20M:1	Frequency Vertical:	24 ~ 75Hz
Light Source:		VIDEO INPUT	
Brightness:	350 cd/m ² (typ)	Digital Sync:	TMDS - HDMI (v2.0), PCI-E - DisplayPort (v1.4), Micro-Packet - Type C
Colours:	1.07B	ERGONOMICS	
Colour Space Support:	10 bit (8 bit + A-FRC)	Height Adjust (mm):	130
Aspect Ratio:	16:9	Swivel:	120°
Response Time (Typical GTG):	5ms	Tilt (Forward/Back):	-5° / 21°
Response Time (GTG w/OD):	5ms	Pivot (Right/Left):	90° / 90°
Viewing Angles:	178° horizontal, 178° vertical	WEIGHT (IMPERIAL)	
Backlight Life (Hours):	30000 Hrs (Min)	Net (lbs):	24
Curvature:	Flat	Net Without Stand (lbs):	15.8
Refresh Rate (Hz):	60	Gross (lbs):	33.7
Adaptive Sync:	Yes	WEIGHT (METRIC)	
Blue Light Filter:	Yes	Net (kg):	10.9
Flicker-Free:	Yes	Net Without Stand (kg):	7.2
Colour Gamut:	Adobe RGB: 95% size / 82% coverage (Typ)DCI-P3: 95% size / 90% coverage (Typ)EBU: 127% size / 100% coverage (Typ)REC709: 128% size / 100% coverage (Typ)SMPTE-C: 139% size / 100% coverage (Typ)NTSC: 91% size (Typ)sRGB: 128% size / 100% coverage (Typ)	Gross (kg):	15.3
Pixel Size:	0.182 mm (H) x 0.182 mm (V)	DIMENSIONS (IMPERIAL) (WXHxD)	
Surface Treatment:	Anti-Glare, Hard Coating (3H)	Packaging (in.):	33.1 x 20.5 x 12.8
COMPATIBILITY		Physical (in.):	28.2 x 20.23-25.35 x 10.4
PC Resolution (max):	3840x2160	Physical Without Stand (in.):	28.2 x 16.7 x 2.6
Mac® Resolution (max):	3840x2160	DIMENSIONS (METRIC) (WXHxD)	
PC Operating System:	Windows 11 certified; macOS tested	Packaging (mm):	840 x 520 x 326
Mac® Resolution (min):	3840x2160	Physical (mm):	715 x 513.8-643.8 x 265
CONNECTOR		Physical Without Stand (mm):	715 x 423 x 66
USB 3.2 Type A Down Stream:	2	GENERAL	
USB 3.2 Type B Up Stream:	1	Regulations:	cTUVus, FCC-B, ICES003, Energy Star 8.0, EPEAT Silver, CEC, NOM, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA, BSMI, CCC, China RoHS, China Energy Label
USB 3.2 Type C Up Stream; DisplayPort Alt mode :	1	PACKAGE CONTENTS:	
HDMI 2.0 (with HDCP 2.2):	2	VP3256-4K x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v2.0, Male-Male) x1, DisplayPort Cable (v1.2; Male-Male) x1, USB Type-C Cable (Male-Male) x1, USB A/B Cable (v3.2; Male-Male) x1, Quick Start Guide x1	
DisplayPort:	1	Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
Power in:	3-pin Socket (IEC C14 / CEE22)	Warranty:	*Warranty offered may differ from market to market
AUDIO		Power Management:	Energy Star standards, EPEAT
Internal Speakers:	3Watts x2	POWER	
Eco Mode (Conserve):	32W	Eco Mode (Conserve):	32W
Eco Mode (optimised):	39W	Eco Mode (optimised):	39W
Consumption (typical):	46W	Consumption (typical):	46W
Consumption (max):	50W	Voltage:	AC 100-240V
Voltage:	AC 100-240V	Stand-by:	0.5W
Stand-by:	0.5W	Power Supply:	Internal Power Supply
ADDITIONAL HARDWARE		CONTROLS	
Kensington Lock Slot:	1	Physical Controls:	Key 1, Key 2, Key 3, Key 4, Key 5, Key 6 (power)
Cable Organisation:	Yes	On Screen Display:	Input Select, Audio Adjust, ViewMode, Colour Adjust, Manual Image Adjust, Setup Menu