





Key Features

- Fast Warm Boot** eliminates long startup delays, launching signage and content in under 7 seconds.
- Native 4K UHD in Any Orientation** delivers sharp, high-resolution visuals in landscape or portrait.
- USB media playback & scheduling with automatic failover** ensures uninterrupted signage
- Commercial-Grade Brightness & 24/7 Reliability** keep content clear and visible around the clock.
- Centralized control** with Pro-AV integration and remote management via Web UI and ViewSonic Manager.



Product Description

The ViewSonic CDE31 Series is a turnkey, commercial-grade digital display that delivers impactful communication across corporate, retail, education, and healthcare environments. With native 4K Ultra HD resolution and reliable 24/7 operation, it delivers sharp, consistent visuals in both landscape and portrait orientations—ideal for digital signage and meeting spaces. Powered by Android 14 OS and a next-generation Quad-Core SoC with 8GB RAM, the CDE31 Series ensures smooth playback and responsive performance for continuous content delivery. The platform is upgradeable to Android 16, supporting ongoing security updates and long-term compatibility. For streamlined deployment and management, it offers seamless ProAV integration with leading control systems, dual 16W built-in speakers, 3.5 mm audio in/out. It also supports static IP configuration, a simplified web-based UI, and centralized remote control via ViewSonic Manager.



1. Speaker	8. USB Type-C	15. Audio Out
2. AC IN	9. HDMI Out	16. Control Panel
3. Power Switch	10. USB2.0 x1, USB3.2 Gen x1	17. OPS Slot
4. WiFi Slot	11. RS232	18. VESA® Wall Mount (600x400mm)
5. HDMI 1	12. LAN	
6. HDMI 2	13. SPDIF	
7. HDMI 3	14. Audio In	

Visit Us

www.viewsonic.com

DISPLAY		ERGONOMICS	
Panel Size:	65"	Wall Mount (VESA®):	600x400 mm
Type/ Tech:	TFT LCD module with DLED backlight	OPERATING CONDITIONS	
Display Area (mm):	1428.48(H) x 803.52(V) 64.5" diagonal	Temperature (° C):	0 to 40°C
Native Resolution:	3840x2160	Humidity:	20%-80% RH
Aspect Ratio:	16:9	OPERATING HOURS	24/7
Colors:	8bit+2bitFRC	DIMENSIONS (W X H X D)	
Brightness:	500 nits	Physical (inch / mm):	57.61 x 31.75 x 2.68 in/ 1463.3 x 806.5 x 68 mm
Contrast Ratio:	1200:1 (typ.) / 5000:1 (DCR enabled)	Packaging (inch / mm):	64.09 x 37.09 x 7.28 in/ 1628 x 942 x 185 mm
Response Time:	6.5ms	WEIGHT	
Viewing Angles:	H = 178, V = 178 typ.	Net (lb / kg):	52.58lb / 23.85kg
Backlight Life:	50,000 Hours	Gross (lb / kg):	70.9lb / 32.16kg
Surface Treatment:	Anti-Glaire, 3H hardness, Haze 25%	REGULATIONS	
Bezel:	15.9mm/15.9mm/15.9mm/15.9mm (L/R/T/B)	cTUVus, FCC/ICES003, Energy star 8, EPEAT Gold, EEI, EMC/CE Report, CB, EAC, UkrSEPRO, RCM, Green BOM, RoHS DoC, ErP-Eco, REACH DoC, SCIP, WEEE report, Annex I, Annex II, TPCH DoC, Packing waste, CA65 DoC	
Orientation:	Landscape & Portrait	ENERGY STAR	ES8.0
PLATFORM		EEI RATING	
Processor:	Quad-core ARM Cortex-A73	F	
RAM:	8GB DDR4	PACKAGE CONTENTS	
Storage:	32GB	1. 3m power cord by ship area 2. Remote control 3. AAA battery x 2 4. Quick Start Guide 5. RS232 adapter 6. Clamp x 5 7. wall mount Screw x 4 8. HDMI cable 3m(HDMI LA certified) 9. Compliance statement	
INPUT			
HDMI:	x3 (HDMI 2.0*3, HDMI1 support ARC)		
Audio:	3.5mm X 1		
RS-232:	x 1		
OPS Slot:	OPS slot x1		
WiFi Slot:	WIFI slot x1		
OUTPUT			
HDMI:	x 1		
Audio:	3.5mm x1 (Line out)		
SPDIF:	x 1		
LAN			
RJ45:	x 2 (*1 LAN-in & *1 LAN-out) 10/100M for USB TypeC, 1000M for OPS		
USB			
Type A:	x 2 (USB2.0 x1, USB3.2 Gen1 x1)		
Type C:	x 1 (PD65W/15W with OPS + DP1.2 + Data USB2.0 + 10M/100M sharing)		
SPEAKERS			
16W x 2			
COMPATIBILITY			
HDMI:	3840X2160 @60Hz		
EMBEDDED OS			
Android 14 AOSP			
BUNDLED SOFTWARE			
Wireless Presentation:	AirSync		
Device Management:	Manager		
POWER			
Voltage:	100-240 VAC +/- 10%		
Consumption:	74.23W with Energy Star		