

PROJECTORS  
**M1**


## Key Features

Advanced LED Light Source | 360-degree projection  
with Smart Stand | Dual Harman Kardon Speakers |  
USB Type-C for Video and Power | Built-in Battery  
with a 2.5 hour lifespan



## Product Description


The ViewSonic® M1 is an ultra-portable LED projector that delivers convenient entertainment in nearly any room. With a built-in battery and over 30,000 hours of operational life, this projector will deliver years of multimedia entertainment wherever it goes. Weighing less than two pounds, the M1's compact and lightweight design makes it ideal for moving from room to room, or for indoor/outdoor usage. An integrated smart stand provides for simple 360-degree setup, while also doubling as a lens cover. Once the lens is uncovered, the projector automatically powers on with full brightness for instant entertainment. The lens also features a safety auto-off feature that powers down the projector when objects are detected too close to the lens. Dual Harman Kardon speakers provide crisp and clear sound for multimedia content, while a short throw lens can display large images in small spaces. What's more, versatile connectivity options include a MicroSD card slot, USB Type-A, and USB Type-C – making the M1 a great option for sharing and displaying videos and other multimedia content.



854 x 480  
**RESOLUTION**



250  
**LUMENS**



1.2  
**THROW RATIO**

### Contact Sales

- call: 888.881.8781
- email: [salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)
- visit: [viewsonic.com](http://viewsonic.com)

**Display:**

|                                    |                             |
|------------------------------------|-----------------------------|
| Type:                              | DLP                         |
| Resolution Type:                   | WVGA                        |
| Resolution:                        | 854 x 480                   |
| Brightness (ANSI Lumens):          | 250                         |
| Throw Distance:                    | 40 in / 1.0 m               |
| Throw Ratio:                       | 1.2                         |
| Display Size (in.):                | 24 - 100 in. / 0.6 - 2.54 m |
| Keystone:                          | Vertical (± 40°)            |
| Lens:                              | Fixed Zoom                  |
| Light Source (watt):               | 10                          |
| Light Source Life, Normal (hours): | 3000                        |
| Color Depth:                       | 1.07B Color (R/G/B 10bit)   |
| Dynamic Contrast Ratio:            | 12,000:1                    |
| Aspect Ratio:                      | 16:9                        |

**Video Signal:**

|                       |            |
|-----------------------|------------|
| Frequency Horizontal: | 15h~135kHz |
| Frequency Vertical:   | 23~120Hz   |

**Compatibility:**

|                        |             |
|------------------------|-------------|
| PC Resolution (max):   | 1920 x 1080 |
| PC Resolution (min):   | 640 x 480   |
| Mac® Resolution (max): | 1920 x 1080 |
| Mac® Resolution (min): | 640 x 480   |

**Connector:**

|  |
|--|
| USB 2.0 Type A(1), USB 3.1 Type C(1), Card Reader(Micro SD), 3.5mm Audio Out(1), HDMI 1.4(1) |
|--|

**Audio:**

|                    |         |
|--------------------|---------|
| Internal Speakers: | 3W (x2) |
|--------------------|---------|

**Power:**

|                        |             |
|------------------------|-------------|
| Voltage:               | 100-240 VAC |
| Consumption (typical): | 55W         |
| Stand-by:              | <0.5W       |

**Controls:**

|                    |  |
|--------------------|--|
| Physical Controls: | Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source                  |
| On Screen Display: | Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality) |

**Operating Conditions:**

|                            |                       |
|----------------------------|-----------------------|
| Temperature:               | 32-104° F (0 - 40° C) |
| Humidity (non-condensing): | 0-90%                 |

**Weight (imperial):**

|            |     |
|------------|-----|
| Net (lbs): | 1.7 |
|------------|-----|

**Weight (metric):**

|           |     |
|-----------|-----|
| Net (kg): | 0.8 |
|-----------|-----|

**Dimensions (imperial) (WxHxD):**

|                 |                 |
|-----------------|-----------------|
| Physical (in.): | 5.8 x 1.6 x 5.0 |
|-----------------|-----------------|

**Dimensions (metric) (WxHxD):**

|                |                  |
|----------------|------------------|
| Physical (mm): | 148 x 40.5 x 126 |
|----------------|------------------|

**General:**

|  |
|--|
| Regulations: FCC, cTUVus, ROHS, TUV-S, NOM, UL2054 |
|--|

PACKAGE CONTENTS: M1 projector, power cable, VGA cable, remote control, Quick Start Guide

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

UPC: 766907000658

**Accessories:**

|               |
|---------------|
| PGD-350, VC10 |
|---------------|