

ViewSonic®

LCD DISPLAY

VG2719U-4K

Key Features

- SuperClear® IPS panel with 4K UHD 3840 X 2160 resolution
- USB hub with 1 upstream, 3 downstream ports, and 2 HDMI, DisplayPort, and USB-C inputs for easy connectivity and up to 96W power delivery
- Super-narrow bezel with dual 3W speakers
- Ergonomic tilt, swivel, pivot, and height adjustment capabilities
- TCO, EnergyStar certified for sustainability



Product Description

The ViewSonic VG2719U-4K is a 27" 4K UHD USB-C monitor designed for professional workspaces. Its SuperClear® IPS panel delivers sharp detail and consistent color performance, complemented by a super-narrow bezel for a clean, modern look. Dual 3W speakers provide clear everyday audio. Connectivity includes USB-C, two HDMI ports, DisplayPort, one USB Type-B upstream, and three USB Type-A downstream ports. An integrated USB hub supports data transfer and up to 96W power delivery through a single cable, simplifying setup and reducing desk clutter. Eye-care technology and full ergonomic adjustability, including height, tilt, swivel, and pivot, ensure lasting comfort during long workdays. The monitor meets ENERGY STAR®, and TCO certifications.

1. Menu Control Panel

2. Speakers

3. VESA Compatible(Wall Mount 100 x 100 mm)

4. Power In

5. HDMI*2

6. DisplayPort
7. USB-C

8. Audio Out

9. USB-B

10. USB-A*3

Visit Us www.viewsonic.com

DISPLAY

Display Size (in.):	27
Viewable Area (in.):	27
Panel Type:	IPS Technology
Resolution:	3840 x 2160
Resolution Type:	UHD (Ultra HD)
Static Contrast Ratio:	1,000:1 (typ)
Dynamic Contrast Ratio:	80M:1
High Dynamic Range:	HDR10
Light Source:	LED
Brightness:	350 cd/m² (typ)
Colors:	1.07B
Color Space Support:	10 bit (8 bit + FRC)
Aspect Ratio:	16:9
Response Time (Typical GTG):	4ms
Response Time (GTG w/OD):	3.965ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	Flat
Refresh Rate (Hz):	60
Low Blue Light:	Software solution
Flicker-Free:	Yes
Color Gamut:	DCI-P3: 88% coverage (Typ) NTSC: 85% size (Typ) sRGB: 120% size (Typ)
Pixel Size:	0.155 mm (H) x 0.155 mm (V)
Surface Treatment:	Anti-Glare, Hard Coating (3H)

COMPATIBILITY

PC Resolution (max):	3840x2160
Mac® Resolution (max):	3840x2160
PC Operating System:	Windows 10/11 certified; macOS tested
Mac® Resolution (min):	3840x2160

CONNECTOR

USB 3.2 Type A Down Stream:	3
USB 3.2 Type B Up Stream:	1
USB 3.2 Type C DisplayPort Alt mode only :	1 (96W power charger)
3.5mm Audio Out:	1
HDMI 2.1:	2
DisplayPort:	1
Power in:	DC Socket (Center Positive)

AUDIO

Internal Speakers:	3Watts x2
--------------------	-----------

POWER

Eco Mode (Conserve):	24W
Eco Mode (optimized):	28W
Consumption (typical):	34W
Consumption (max):	36W
Voltage:	AC 100-240V
Stand-by:	0.5W
Power Supply:	External Power Adaptor

ADDITIONAL HARDWARE

Kensington Lock Slot:	1
Cable Organization:	Yes

CONTROLS

Physical Controls:	Key 1, Key 2, Key 3, Key 4, Key 5, Key 6 (power)
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu

OPERATING CONDITIONS

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity (non-condensing):	20% to 90%

WALL MOUNT

VESA Compatible:	100 x 100 mm
------------------	--------------

INPUT SIGNAL

Frequency Horizontal:	15 ~ 160KHz
Frequency Vertical:	40 ~ 75Hz

VIDEO INPUT

Digital Sync:	TMDS - HDMI (v2.1), PCI-E - DisplayPort (v1.4), Micro-Packet - Type C
---------------	---

ERGONOMICS

Height Adjust (mm):	150
Swivel:	90°
Tilt (Forward/Back):	-5° / 20°
Pivot (Right/Left):	90° / 90°

WEIGHT (IMPERIAL)

Net (lbs):	13.7
Net Without Stand (lbs):	9.3
Gross (lbs):	18.5

WEIGHT (METRIC)

Net (kg):	6.2
Net Without Stand (kg):	4.2
Gross (kg):	8.4

DIMENSIONS (IMPERIAL) (WXHxD)

Packaging (in.):	33.3 x 20 x 5.6
Physical (in.):	24.14 x 16.02~21.92 x 8.42
Physical Without Stand (in.):	24.14 x 14.22 x 2.05

DIMENSIONS (METRIC) (WXHxD)

Packaging (mm):	846 x 508 x 141
Physical (mm):	613.1 x 406.9~556.9 x 213.9
Physical Without Stand (mm):	613.1 x 361.3 x 52

GENERAL

Regulations:	Energy Star, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, TCO 10.0 for VSE, EAC, UkrSEPRO, BSMI
PACKAGE CONTENTS:	VG2719U-4K x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v2.0; Male-Male) x1, USB Type-C Cable (Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1
Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
Warranty:	*Warranty offered may differ from market to market
Power Management:	Energy Star standards