## Key **Features**

4K Ultra HD Resolution | High Dynamic Range | Seamless Viewing Experience | Loaded with Connectivity (with HDCP 2.2) | Amazing Color Accuracy



## Product **Description**

Perfect for photographers, designers, videographers, and other creative professionals, the ViewSonic\* VP2768-4K Ultra HD monitor delivers unmatched color accuracy and reliable long-term performance. With a SuperClear PIPS panel and a sleek frameless design, this monitor provides a near-seamless viewing experience ideal for multimonitor setups. To ensure precise, uniform color, each of our monitors is factory calibrated to deliver an amazing Delta E<2 value for superior color accuracy. An integrated to deliver an amazing Delta E<2 value for superior color accuracy. $color \, uniformity \, function \, ensures \, consistent \, chromaticity \, across \, the \, screen, \, while \, a \, 14-bit \, 3D \, look-up \, table \, generates \, a \, stunningly \, smooth \, palette \, of \, 4.39 \, trillion \, colors. \, Add \, colors \, and \, colors \, col$ to that 6-axis color adjustment functionality, and this monitor provides the ultimate color processing capability for professional applications. What's more, productivityboosting features include an advanced ergonomic design. Hardware calibration is also available with the optional ViewSonic Colorbration Kit, which allows you to quickly  $and\ easily\ calibrate\ the\ monitor\ for\ photography,\ graphic\ design,\ content\ creation,\ and\ other\ color-critical\ applications.$ 









**PANEL** 



3840 x 2160 RESOLUTION



- call: 888.881.8781
- Contact Sales email: salesinfo@viewsonic.com
  - visit: viewsonic.com

Despite   2004   100 m   100	Display:		Mount:		Award
Panel Type:	Display Size (in.):	27	VESA Compatible:	100 x 100 mm	
Second part	Viewable Area (in.):	27	Video Signal:		Vid
Static Contrast Ratio:   1,300.1   2,000.000.1   0,100	Panel Type:	IPS	Frequency Horizontal:	15 ~136KHz	-
Opmanic Contrast failor         20,000,000-1         Digital Syrec         TMDS for HDMR, PCI-E for DisplayPort / Mini Display Port           Light Source         WEED         Ergonomics:           Brightness:         350 cdm²         Height Adjust (mm):         130           Colors:         1,078         Swwee         120°           Color Space Support:         10 8tt with FRC         Nev (Right/Left):         90° 90°           Aspect Ratio:         16-9         Tit (Forward/Back):         21″ 5°           Aspect Ratio:         16-9         Net Oblis:         15.2           Response Time (GTG w/OD):         7ms         Net Without Stand (lib):         3.3           Wewing Angles:         179° hortzontal, 178° vertical         Net Without Stand (lib):         2.3           Backlight Life (Hours):         30,000         Gross (lib):         2.2.3           Compatibility:         Net Without Stand (lig):         4.2           Compatibility:         Net Without Stand (lig):         4.2           Commetcion:         Jake 3 × 2160         Her Without Stand (lig):         2.2.3           Commetcion:         Jake 3 × 2160         Her Without Stand (lig):         2.2.3           Commetcion:         Physical Without Stand (lig):         2.2.3 × 10.6 × 18.1      <	Resolution:	3840 x 2160	Frequency Vertical:	24 ~ 75Hz	
	Static Contrast Ratio:	1,300:1	Video Input:		
Light Source:         MED         Egrommics:         130           Brightness:         350 cd/m2         Height Adjust (mm):         130           Colors:         10 Bit with FRC         Swivel:         120 Po           Color Space Support:         16 9         Tilt (Forward/Back):         217 5°           Response Time (Typical GTG):         14ms         Weight (imperial):         217 5°           Response Time (GTG WOD):         7ms         Net (light Cinct):         9.3           Backlight Life (Hours):         30,000         Gross (lbs):         22.3           Panel Surface:         Anti-glane, Hard coasting (3H)         Weight (metric):         22.3           Compatibility:         Net (light Cinct):         4.9           PR Resolution (max):         3840 x 2160         Net Without Stand (ligh:         4.2           PR Resolution (max):         3840 x 2160         Net Without Stand (ligh:         4.2           Stand Tippe A(d), USB 3.1 Type B(1): 3.5m Audio Out(1), HDMI 20(2), Display Port(1)         Packaging (mix):         42.8 3 x 10.6 x 18.1           Prover Compatibility:         19 Provided (merce):         42.2 x 13.3 x 8.5         1.9           Consumption (fypical):         38.5         Provided (merce):         42.3 x 13.3 x 3.0         2.2 x 13.3 x 8.5	Dynamic Contrast Ratio:	20,000,000:1	Digital Sync:		
Colors:   1.078	Light Source:	WLED	Ergonomics:		
Color Space Support:   10 Bit with FRC   Proot (Right/Left):   90°, 90°	Brightness:	350 cd/m2	Height Adjust (mm):	130	
Aspect Ratio: 16-9 Tilt (Forward/Back): 214 5 ° Response Time (Typical GTG): 14ms	Colors:	1.07B	Swivel:	120°	
Response Time (Typical GTG):	Color Space Support:	10 Bit with FRC	Pivot (Right/Left):	90° / 90°	
Response Time (6TG w/OD):         7ms         Net (lbs):         15.2           Viewing Angles:         178° horizontal, 178° vertical         Net Without Stand (lbs):         9.3           Backlight Life (Hours):         30,000         Gross (lbs):         22.3           Panel Surface:         Anti-glare, Hard coating (3H)         Weight (metric):         22.3           Compatibility:         Net (kg):         6.9           PC Resolution (max):         3840 x 2160         Net Without Stand (kg):         4.2           Connector:         Dimensions (imperial) (WxHxD):         22.3           Connector:         Dimensions (imperial) (WxHxD):         22.3           Consultion (max):         3840 x 2160         Gross (kg):         2.2         2.2           Consultion (max):         3840 x 2160         Gross (kg):         2.2         2.2         2.2           Consultion (max):         3840 x 2160         Provided (in:):         4.2         2.2 </td <td>Aspect Ratio:</td> <td>16:9</td> <td>Tilt (Forward/Back):</td> <td>21º/ 5º</td> <td></td>	Aspect Ratio:	16:9	Tilt (Forward/Back):	21º/ 5º	
Net Without Stand (libs): 9.3	Response Time (Typical GTG):	14ms	Weight (imperial):		
Backlight Life (Hours):         30,000         Gross (lbs):         22.3           Panel Surface:         Anti-glare, Hard coating (3H)         Weight (metric):           Compatibility:         Net (kg):         6.9           PC. Resolution (max):         3840 x 2160         Net Without Stand (kg):         4.2           Connector:         Dimensions (imperial) (WXHXD):         2.3           Connector:         Dimensions (imperial) (WXHXD):         Packaging (in):         28.3 x 10.6 x 18.1           Mini Display Port(1)         Packaging (in):         28.3 x 10.6 x 18.1           Power:         Physical (in):         24.2 x 21.3 x 8.5           Prower:         Physical (in):         24.2 x 21.3 x 8.5           Eco Mode (Conserve):         29         Dimensions (metric) (WXHXD):           Eco Mode (Conserve):         38.5         Dimensions (metric) (WXHXD):         720.0 x 268.0 x 460.0           Consumption (max):         46         Physical (min):         720.0 x 268.0 x 460.0           Consumption (max):         48         Physical (min):         613.0 x 540.6 x 215.0           Stand-by:         0.5         Regulations: CTUVus, FCC-8, Mexico Energy, EPEAT GOLD, Energy Star           Power Supply:         10         Packaging (min):         720.0 x 68.0 x 450.0           Addit	Response Time (GTG w/OD):	7ms	Net (lbs):	15.2	
Panel Surface: Anti-glare, Hard coating (3H)  Compatibility: Net (kg): 6.9  Resolution (max): 3840 x 2160  Mac* Resolution (max): 3840 x 2160  Connector: Dimensions (imperial) (WxHxD): 2.2.3  Connector: Dimensions (imperial) (WxHxD): 2.2.3  Connector: Dimensions (imperial) (WxHxD): 2.2.3 x 8.5  Power: Physical (in.): 24.2 x 21.3 x 8.5  Physical (in.): 24.2 x 21.3	Viewing Angles:	178° horizontal, 178° vertical	Net Without Stand (lbs):	9.3	
Compatibility:         Net (kg):         6.9           PC Resolution (max):         3840 x 2160         Net Without Stand (kg):         4.2           Connector:         Dimensions (imperial) (WxHxD):         22.3           Connector:         Dimensions (imperial) (WxHxD):         28.3 x 10.6 x 18.1           USB 3.1 Type R4(4), USB 3.1 Type B(1), 3.5 mm Audio Out(1), HDMI 2.0(2), Display Port(1), Mini Display Port(1)         Packaging (in):         28.3 x 10.6 x 18.1           Power:         Physical (in):         24.2 x 21.3 x 8.5         Permonential (in):         24.2 x 21.3 x 8.5           Power:         Physical (in):         24.2 x 21.3 x 8.5         Permonential (in):         24.2 x 21.3 x 8.5           Eco Mode (Conserve):         29         Dimensions (metric) (WxHxD):         24.2 x 21.3 x 8.5         Permonential (in):         24.2 x 21.3 x 8.5         Physical (in):         24.2 x 21.3 x 8.5         Permonential (in):         24.2 x 21.3 x 8.5         Physical (in):         24.2 x 21.3 x 8.5         Physical (in):         24.2 x 21.3 x 8.5         Permonential (in):         24.2	Backlight Life (Hours):	30,000	Gross (lbs):	22.3	
PC Resolution (max):	Panel Surface:	Anti-glare, Hard coating (3H)	Weight (metric):		
Mac* Resolution (max): 3840 x 2160  Gross (kg): 22.3  Dimensions (imperial) (WXHXD):  USB 3.1 Type A(4), USB 3.1 Type B(1), 3.5mm Audio Out(1), HDMI 2.0(2), Display Port(1), Packaging (in.): 28.3 x 10.6 x 18.1  Physical (in.): 24.2 x 21.3 x 8.5  Physical Without Stand (in.): 24.1 x 13.9 x 2.0  Dimensions (metric) (WXHXD):  Packaging (m.): 24.2 x 21.3 x 8.5  Physical Without Stand (in.): 24.1 x 13.9 x 2.0  Dimensions (metric) (WXHXD):  Packaging (mm): 720.0 x 268.0 x 460.0  Physical (mm): 613.0 x 540.6 x 215.0  Physical (mm): 613.0 x 540.6 x 215.0  Physical (mm): 613.0 x 540.6 x 215.0  Physical Without Stand (mm): 613.0 x 353.4 x 50.3  General:  Stand-by: 0.5  Power Supply: Internal  Additional Hardware: USB 3.1 Up Stream Cable, Quick Start Guide, ViewSoinc Wizard CD-ROM  Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.  Controls: Warranty: Three-year limited warranty on parts, labor and backlight  UPC: 766907000832  Auto Image Adjust, Colort Adjust, Information, Manual Image Adjust, Color Adjust, Information, Complete OSD functionality)  Departing Conditions:  Temperature: 32-104° F (0 - 40° C)	Compatibility:		Net (kg):	6.9	
Dimensions (imperial) (WxHxD):  USB 3.1 Type A(4), USB 3.1 Type B(1), 3.5mm Audio Out(1), HDMI 2.0(2), Display Port(1), Mini Display Port(1)  Power:  Eco Mode (Conserve): 29  Eco Mode (optimized): 38.5  Consumption (typical): 46  Consumption (typical): 48  Voltage: AC 100-240V (universal), 50-60Hz  Stand-by: 0.5  Power Supply: Internal  Additional Hardware:  Kensington Lock Slot: 1  Controls: 1,2,3,4,5,Power  Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)  Diperating Conditions:  Temperature: 32-104° F (0 - 40° C)  Pissical (in.): 28.3 x 10.6 x 18.1  Physical (in.): 24.1 x 13.9 x 2.0  Dimensions (metric) (WxHxD):  Packaging (in.): 24.2 x 21.3 x 8.5  Physical (in.): 24.2 x 13.8 y 2.0  Dimensions (metric) (WxHxD):  Packaging (mm): 720.0 x 268.0 x 460.0  Physical (in.): 24.1 x 13.9 x 2.0  Dimensions (metric) (WxHxD):  Packaging (mm): 720.0 x 268.0 x 460.0  Physical (in.): 24.2 x 13.8 y 2.0  Dimensions (metric) (WxHxD):  Packaging (in.): 24.2 x 13.8 y 2.0  Dimensions (metric) (WxHxD):  Packaging (mm): 720.0 x 268.0 x 460.0  Physical (in.): 24.1 x 13.9 x 2.0  Dimensions (metric) (WxHxD):  Packaging (mm): 720.0 x 268.0 x 460.0  Physical (in.): 24.1 x 13.9 x 2.0  Dimensions (metric) (WxHxD):  Packaging (mm): 720.0 x 268.0 x 460.0  Physical (in.): 24.1 x 13.9 x 2.0  Dimensions (metric) (WxHxD):  Packaging (mm): 720.0 x 268.0 x 460.0  Physical (in.): 24.1 x 13.9 x 2.0  Dimensions (metric) (WxHxD):  Packaging (mm): 720.0 x 268.0 x 460.0  Physical (in.): 24.1 x 13.9 x 2.0  Dimensions (metric) (WxHxD):  Packaging (mm): 720.0 x 268.0 x 460.0  Physical (in.): 24.1 x 13.9 x 2.0  Dimensions (metric) (WxHxD):  Packaging (mm): 720.0 x 268.0 x 460.0  Physical (in.): 24.1 x 13.9 x 2.0  Dimensions (metric) (WxHxD):  Packaging (mm): 720.0 x 268.0 x 460.0  Physical (in.): 24.1 x 13.9 x 2.0  Physical (in.): 24.1 x 13.9 x 2.0  Physical (in.): 24.1 x 13.9 x 2.0  Physical (i	PC Resolution (max):	3840 x 2160	Net Without Stand (kg):	4.2	
USB 3.1 Type A(4), USB 3.1 Type B(1), 3.5mm Audio Out(1), HDMI 2.0(2), Display Port(1), Mini Display Port(1)  Physical (in.): 24.2 x 21.3 x 8.5  Physical Without Stand (in.): 24.1 x 13.9 x 2.0  Dimensions (metric) (WxHxD):  Packaging (mm): 720.0 x 268.0 x 460.0  Physical (mm): 720.0 x 268.0 x 460.0  Physical (mm): 613.0 x 540.6 x 215.0  Physical (mm): 613.0 x 353.4 x 50.3  Dimensions (metric) (WxHxD):  Packaging (mm): 720.0 x 268.0 x 460.0  Physical (mm): 613.0 x 353.4 x 50.3  Dimensions (metric) (WxHxD):  Packaging (mm): 720.0 x 268.0 x 460.0  Physical (mm): 613.0 x 353.4 x 50.3  Dimensions (metric) (WxHxD):  Packaging (mm): 720.0 x 268.0 x 460.0  Physical (mm): 613.0 x 353.4 x 50.3  Dimensions (metric) (WxHxD):  Packaging (mm): 720.0 x 268.0 x 460.0  Physical (mm): 613.0 x 353.4 x 50.3  Dimensions (metric) (WxHxD):  Packaging (mm): 720.0 x 268.0 x 460.0  Physical (mm): 613.0 x 353.4 x 50.3  Dimensions (metric) (WxHxD):  Packaging (mm): 720.0 x 268.0 x 460.0  Physical (mm): 613.0 x 353.4 x 50.3  Dimensions (metric) (WxHxD):  Packaging (mm): 720.0 x 268.0 x 460.0  Physical (mm): 613.0 x 353.4 x 50.3  Dimensions (metric) (WxHxD):  Packaging (mm): 720.0 x 268.0 x 460.0  Physical (mm): 613.0 x 353.4 x 50.3  Dimensions (metric) (WxHxD):  Packaging (mm): 720.0 x 268.0 x 460.0  Physical (mm): 613.0 x 353.4 x 50.3  Dimensions (metric) (WxHxD):  Packaging (mm): 720.0 x 268.0 x 460.0  Physical (mm): 613.0 x 353.4 x 50.3  Dimensions (metric) (WxHxD):  Packaging (mm): 720.0 x 268.0 x 460.0  Physical (mm): 613.0 x 353.4 x 50.3  Dimensions (metric) (WxHxD):  Packaging (mm): 720.0 x 268.0 x 460.0  Physical (mm): 613.0 x 353.4 x 50.3  Dimensions (metric) (WxHxD):  Packaging (mm): 720.0 x 268.0 x 460.0  Physical (mm): 613.0 x 353.4 x 50.3  Dimensions (metric) (WxHxD):  Packaging (mm): 720.0 x 268.0 x 460.0  Physical (mm): 720.0 x 268.0 x 26	Mac® Resolution (max):	3840 x 2160	Gross (kg):	22.3	
Mini Display Port(1)  Physical (in.): 24.2 x 21.3 x 8.5  Physical (without Stand (in.): 24.1 x 13.9 x 2.0  Dimensions (metric) (WxHxD):  Packaging (mm): 720.0 x 268.0 x 460.0  Physical (mm): 613.0 x 540.6 x 215.0  Physical Without Stand (mm): 613.0 x 353.4 x 50.3  General:  Regulations: cTUVus, FCC-8, Mexico CoC, Mexico Energy, EPEAT GOLD, Energy Star Packagitions (TuVus, FCC-8, Mexico CoC, Mexico Energy, EPEAT GOLD, Energy Star Packagitions (TuVus, FCC-8, Mexico Energy, EPEAT GOLD, Energy Star Packagitions (TuVus, FCC-8, Mexico Energy, EPEAT GOLD, Energy Star Packagitions (TuVus, FCC-8, Mexico Energy, EPEAT GOLD, Energy Star Packagitions (TuVus, FCC-8, Mexico Energy, EPEAT GOLD, Energy Star Packagitions (TuVus, FCC-8, Mexico Energy, EPEAT GOLD, Energy Star Packagitions (TuVus, FCC-8, Mexico Energy, EPEAT GOLD, Energy Star Packagitions (TuVus, FCC-8, Mexico Energy, EPEAT GOLD, Energy Star Packagitions (TuVus, FCC-8, Mexico Energy, EPEAT GOLD, Energy Star Packagitions (TuVus, FCC-8, Mexico Energy, EPEAT GOLD, Energy Star Packagitions (TuVus, FCC-8, Mexico Energy, EPEAT GOLD, Energy Star Packagitions (TuVus, FCC-8, Mexico Energy, EPEAT GOLD, Energy Star Packagitions (TuVus, FCC-8, Mexico Energy, EPEAT GOLD, Energy Star Packagitions (TuVus, FCC-8, Mexico Energy, EPEAT GOLD, Energy Star Packagitions (TuVus, FCC-8, Mexico Energy, EPEAT GOLD, Energy Star Packagitions (TuVus, FCC-8, Mexico Energy, EPEAT GOLD, Energy Star Packagitions (TuVus, FCC-8, Mexico Energy, EPEAT GOLD, Energy Star Packagitions (TuVus, FCC-8, Mexico Energy, EPEAT GOLD, Energy Star Packagitions (TuVus, FCC-8, Mexico Energy, EPEAT GOLD, Energy Star Packagitions (TuVus, FCC-8, Mexico Energy, EPEAT GOLD, Energy Star Packagitions (TuVus, FCC-8, Mexico Energy, EPEAT GOLD, Energy Star Packagitions (TuVus, FCC-8, Mexico Energy, EP	Connector:		Dimensions (imperial) (WxHxD):		
Physical (in.): 24.2 x 21.3 x 8.5  Physical (in.): 24.2 x 21.3 x 8.5  Physical (in.): 24.1 x 13.9 x 2.0  Physical Without Stand (in.): 24.1 x 13.9 x 2.0  Dimensions (metric) (WXHXD):  Packaging (mm): 720.0 x 268.0 x 460.0  Physical (mm): 613.0 x 540.6 x 215.0  Physical (mm): 613.0 x 540.6 x 215.0  Physical (mm): 613.0 x 353.4 x 50.3  General:  Regulations: cTUVus, FCC-8, Mexico CoC, Mexico Energy, EPEAT GOLD, Energy Star  PACKAGE CONTENTS: VP2768-4K Display, Power Cable, Mini DP to DisplayPort Cable, USB 3.1 Up Stream Cable, Quick Start Guide, ViewSoinc Wizard CD-ROM  Controls: Warranty: Three-year limited warranty on parts, labor and backlight  Physical Controls: UPC: 766907000832  Accessories: CB-00009950, CB-00010555, CB-00010684, LCD-CMK-001, LCD-DMA-001, LC			Packaging (in.):	28.3 x 10.6 x 18.1	
Eco Mode (Conserve): 29  Eco Mode (optimized): 38.5  Consumption (typical): 46  Consumption (max): 48  Voltage: AC 100-240V (universal), 50-60Hz  Stand-by: 0.5  Packaging (mm): 720.0 x 268.0 x 460.0  Physical (mm): 613.0 x 353.4 x 50.3  General:  Regulations: cTUVus, FCC-B, Mexico CoC, Mexico Energy, EPEAT GOLD, Energy Star  PACKAGE CONTENTS: VP2768-4K Display, Power Cable, Mini DP to DisplayPort Cable, USB 3.1 Up Stream Cable, Quick Start Guide, ViewSoinc Wizard CD-ROM  Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)  Poperating Conditions:  Temperature: 32-104° F (0 - 40° C)			Physical (in.):	24.2 x 21.3 x 8.5	
Eco Mode (optimized):  2		29	Physical Without Stand (in.):	24.1 x 13.9 x 2.0	
Consumption (typical):  46 Packaging (mm): 720.0 x 268.0 x 460.0 Physical (mm): 613.0 x 540.6 x 215.0 Physical (mm): 613.0 x 353.4 x 50.3 Physical (mm): 613.0 x 353.4 x 50.3 Physical (mm): 613.0 x 353.4 x 50.3  General:  Regulations: cTUVus, FCC-B, Mexico CoC, Mexico Energy, EPEAT GOLD, Energy Star PACKAGE CONTENTS: VP2768-4K Display, Power Cable, Mini DP to DisplayPort Cable, USB 3.1 Up Stream Cable, Quick Start Guide, ViewSoinc Wizard CD-ROM  Additional Hardware:  Kensington Lock Slot: 1 Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.  Controls: Warranty: Three-year limited warranty on parts, labor and backlight  PPC: 766907000832  Auto Image Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)  Accessories:  CD-OWMK-001  CD-WMK-001  CD-WMK-001			Dimensions (metric) (WxHxD)	:	
Physical (mm): 613.0 x 540.6 x 215.0  Physical (mm): 613.0 x 540.6 x 215.0  Physical (mm): 613.0 x 353.4 x 50.3  Physical (mm): 613.0 x 353.4 x 50.3  Physical Without Stand (mm): 613.0 x 353.4 x 50.3  Physical Without Stand (mm): 613.0 x 353.4 x 50.3  General:  Regulations: cTUVus, FCC-B, Mexico CoC, Mexico Energy, EPEAT GOLD, Energy Star  Power Supply: Internal PACKAGE CONTENTS: VP2768-4K Display, Power Cable, Mini DP to DisplayPort Cable, USB 3.1 Up Stream Cable, Quick Start Guide, ViewSoinc Wizard CD-ROM  Kensington Lock Slot: 1 Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.  Controls: Warranty: Three-year limited warranty on parts, labor and backlight  UPC: 766907000832  Auto Image Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)  Coperating Conditions:  Temperature: 32-104° F (0 - 40° C)			Packaging (mm):	720.0 x 268.0 x 460.0	
Voltage: AC 100-240V (universal), 50-60Hz  General:  Stand-by: 0.5 Regulations: cTUVus, FCC-B, Mexico CoC, Mexico Energy, EPEAT GOLD, Energy Star Power Supply: Internal PACKAGE CONTENTS: VP2768-4K Display, Power Cable, Mini DP to DisplayPort Cable, USB 3.1 Up Stream Cable, Quick Start Guide, ViewSoinc Wizard CD-ROM Kensington Lock Slot: 1 Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.  Controls: Warranty: Three-year limited warranty on parts, labor and backlight UPC: 766907000832  Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)  Operating Conditions:  Temperature: 32-104° F (0 - 40° C)			Physical (mm):	613.0 x 540.6 x 215.0	
General:  Stand-by: 0.5 Regulations: cTUVus, FCC-B, Mexico CoC, Mexico Energy, EPEAT GOLD, Energy Star  Power Supply: Internal PACKAGE CONTENTS: VP2768-4K Display, Power Cable, Mini DP to DisplayPort Cable, USB 3.1 Up Stream Cable, Quick Start Guide, ViewSoinc Wizard CD-ROM  Kensington Lock Slot: 1 Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.  Controls: Warranty: Three-year limited warranty on parts, labor and backlight  UPC: 766907000832  Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)  Operating Conditions:  Temperature: 32-104° F (0 - 40° C)			Physical Without Stand (mm):	613.0 x 353.4 x 50.3	
Power Supply:  Internal  Additional Hardware:  Kensington Lock Slot:  Internal  PACKAGE CONTENTS: VP2768-4K Display, Power Cable, Mini DP to DisplayPort Cable, USB 3.1 Up Stream Cable, Quick Start Guide, ViewSoinc Wizard CD-ROM  Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.  Controls:  Warranty: Three-year limited warranty on parts, labor and backlight  UPC: 766907000832  Auto Image Adjust, Color Adjust, Information, Manual Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)  Operating Conditions:  Temperature:  32-104° F (0 - 40° C)	-				
Additional Hardware:  Kensington Lock Slot:  I Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.  Warranty: Three-year limited warranty on parts, labor and backlight  UPC: 766907000832  Auto Image Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)  Operating Conditions:  Temperature:  32-104° F (0 - 40° C)			Regulations: cTUVus, FCC-B, Mexic	to CoC, Mexico Energy, EPEAT GOLD, Energy Star	
Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.  Controls:  Warranty: Three-year limited warranty on parts, labor and backlight  UPC: 766907000832  Auto Image Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)  Operating Conditions:  Temperature:  1 Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.  Warranty: Three-year limited warranty on parts, labor and backlight  UPC: 766907000832  Accessories:  CE-00009950, CB-00010684, LCD-CMK-001, LCD-DMA-001, LCD-DMA-002, LCD-WMK-001  CD-WMK-001		internal			
Controls: Warranty: Three-year limited warranty on parts, labor and backlight  Physical Controls: 1,2,3,4,5,Power  UPC: 766907000832  Auto Image Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)  CB-00009950, CB-00010684, LCD-CMK-001, LCD-DMA-001, LCD-DMA-002, LCD-WMK-001  CD-WMK-001  CD-WMK-001		1	Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.		
Physical Controls: 1,2,3,4,5,Power UPC: 766907000832  Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)  **Degrating Conditions:**  Temperature: 32-104° F (0 - 40° C)  UPC: 766907000832  **Accessories:  CB-00009950, CB-00010555, CB-00010684, LCD-CMK-001, LCD-DMA-001, LCD-DMA-002, LCD-WMK-001	-				
Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)  CB-00009950, CB-00010555, CB-00010684, LCD-CMK-001, LCD-DMA-001, LCD-DMA-002, LCD-WMK-001  CD-WMK-001  CD-WMK-001		1,2,3,4,5,Power			
Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)  CB-00009950, CB-00010555, CB-00010684, LCD-CMK-001, LCD-DMA-001, LCD-DMA-002  LCD-WMK-001  CD-WMK-001  CD-WMK-001  CD-WMK-01		Auto Image Adjust, Contrast/Brightness, Input			
Temperature: 32-104° F (0 - 40° C)	On Screen Display:	Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for	CB-00009950, CB-00010555, CB-00	0010684, LCD-CMK-001, LCD-DMA-001, LCD-DMA-002	!,
	Operating Conditions:				
Humidity (non-condensing): 20-90%	Temperature:	32-104° F (0 - 40° C)			
	Humidity (non-condensing):	20-90%			

Copyright © ViewSonic Corporation 2000-2018. All rights reserved. (09/12/2018 05:20 AM PST)