

INFORMATION

24" 4-side slim bezel IPS monitor with 16:10 WUXGA resolution and 15cm height-adjustable stand


Designed for professionals who demand precision and productivity, the ProLite XB2495WSU-B1 delivers extra vertical workspace and consistent colour accuracy, making it ideal for CAD applications, data analysis, universities, and corporate environments.

The 24" IPS panel with a 16:10 aspect ratio and WUXGA (1920 x 1200) resolution provides more on-screen space than standard Full HD displays. This means you can view detailed drawings, spreadsheets and documents with less scrolling and greater clarity. IPS technology ensures accurate, natural colours and wide viewing angles, so your work looks consistent from every perspective.

For long working days, comfort is essential. The 15cm height-adjustable stand with pivot and swivel functions allows you to tailor the screen position precisely to your needs, supporting better posture and reducing strain. The 4-side slim bezel design not only gives the monitor a modern, professional appearance but also makes it perfect for seamless multi-monitor setups.

Reliable, versatile and built for demanding professional use, the XB2495WSU-B1 helps you work more efficiently while maintaining comfort and visual precision throughout the day.





Gain extra workspace with a 16:10 aspect ratio

With a WUXGA 1920 × 1200 monitor, you can see more rows in Excel, a larger portion of an A4 document, and longer sections of code without constant scrolling. In CAD work, you benefit from a larger drawing area while keeping toolbars visible. You switch views less often and compare data more efficiently, helping you complete reports, analyses, projects, and technical documentation faster.



Adjustable stand for optimal comfort

Find your perfect screen position easily and maintain a healthy, comfortable posture all day long. Thanks to its fully adjustable stand, you can effortlessly adapt the monitor to your needs. Raise or lower the height, swivel left or right, or tilt the screen to reduce glare and find the optimal viewing angle. Whether you're working, designing, or attending long video calls, this flexibility helps reduce neck and back strain, improving both comfort and productivity throughout your day.



Versatile connectivity for all your devices

Connect multiple devices and accessories in one simple step with HDMI, DisplayPort and the USB hub, streamlining your workspace for maximum efficiency and ensuring a tidy, uninterrupted workflow.



Built-in audio without extra clutter

Enjoy clear, pleasant sound for calls, videos, and music while keeping your desk free of extra speakers, thanks to the integrated audio.

SPECIFICATION

01 DISPLAY CHARACTERISTICS

Design	4-side slim bezel
Diagonal	24.1", 61.1cm
Panel	IPS Panel Technology LED, matte finish
Native resolution	1920 x 1200 @100Hz (2.3 megapixel)
Aspect ratio	16:10
Panel brightness	350 cd/m ²
Static contrast	1500:1
Advanced contrast	80M:1
Response time (GTG)	4ms
Viewing zone	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Colour support	16.7mIn (sRGB: 99%; NTSC: 72%)
Horizontal Sync	30 - 135kHz
Viewable area W x H	518.4 x 324mm, 20.4 x 12.8"
Pixel pitch	0.27mm
Colour	matte, black

02 INTERFACES / CONNECTORS / CONTROLS

Signal input	HDMI x1 (v.1.4) DisplayPort x1 (v.1.2)
USB HUB	x4 (3x v.3.2 Gen 1 (5Gbps, 4.5W) 1x Type C (5Gbps, 15W))
HDCP	yes
Headphone connector	yes

03 FEATURES

Flicker free	yes
Extra	i-Style colour, Eye Comfort
OSD languages	EN, DE, FR, ES, IT, CN, RU, JP, CZ, NL, PL, TR, UA
Control buttons	Joystick/Power Button: (Centre) Power/Menu, Up/Input Select, Down, Right/Volume, Left/Show Submenu
User controls	picture adjust (brightness, contrast, ECO, ACR, OD, X-res technology), colour settings (6-axis, i-Style colour, RGB range, colour temp., user preset), OSD (OSD H. position, OSD V. position, OSD rotate, OSD time, OSD background, DDC/CI control, display information), language, extra 1 (sharpness, video mode adjust, opening logo, power LED, USB charge), extra 2 (shortcut key, FW version), input select, audio settings (volume, mute), reset (recall all?)
Speakers	2 x 2W
Convenience	Kensington-lock™ prepared, DDC/CI, DDC2B, Mac OSX

04 MECHANICAL

Display position adjustments	height, swivel, tilt, pivot (rotation both sides)
Height adjustment	150mm
Rotation (PIVOT function)	90°
Swivel stand	120°; 60° left; 60° right
Tilt angle	23° up; 5° down
VESA mounting	100 x 100mm
Cable management system	yes

05 ACCESSORIES INCLUDED

Cables	power (1.8m), USB (1.8m), HDMI (1.8m)
Other	quick start guide, safety guide

06 POWER MANAGEMENT


Power supply unit	internal
Power supply	AC 100 - 240V, 50/60Hz
Power usage	12W typical, 0.5W stand by, 0.3W off mode

07 SUSTAINABILITY

Regulations	TCO Certified, CE, TÜV-GS, EAC, RoHS support, ErP, WEEE, REACH, UKCA
Energy efficiency class (Regulation (EU) 2017/1369)	C
EPEAT Silver	*registration varies by country, go to www.epeat.net for details
REACH SVHC	above 0.1%: Lead

08 DIMENSIONS / WEIGHT

Product dimensions W x H x D	533.5 x 373.5 (521) x 209.5mm
Box dimensions W x H x D	613 x 130 x 437mm
Weight (without box)	4.9kg
Weight (with box)	6.9kg
EAN code	4948570127641





All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects. © **IYAMA CORPORATION. ALL RIGHTS RESERVED**