INFORMATION

27" QHD IPS monitor with 4-side slim bezel, ergonomic stand and USB hub

Designed to support your productivity, the ProLite XB2793QSU helps you stay focused and efficient throughout the day. The 27" QHD resolution (2560×1440) provides more space to work, letting you view documents side by side, edit with precision or keep multiple apps open at once, all in sharp detail.

The IPS panel ensures vivid colours and consistent clarity from any angle. Flicker free technology and a blue light reducer enhance eye comfort during long sessions.

The four side ultra slim bezel design brings a clean, modern look and suits multi monitor setups. The ergonomic stand offers height, tilt, swivel and pivot adjustment for better comfort throughout the day. Built-in speakers, a two-port USB hub, HDMI and DisplayPort inputs, and a headphone socket help reduce desk clutter.

With EPEAT registration and TCO compliance, the XB2793QSU combines reliable performance with responsible energy use.

Expand your view with QHD

QHD 2560x1440 resolution offers up to 77% more screen space than Full HD, giving you plenty of room to multitask efficiently, view more content at once, and work with greater precision, without constantly switching between windows.

Multi-screen setup for a panoramic workspace

Connect multiple ultra-slim bezel monitors to create a panoramic workspace, keep your apps in view, streamline multitasking, and boost productivity.

Adjustable stand for optimal comfort

Find your perfect screen position easily and maintain a healthy, comfortable posture all day long. Thanks to its fully adjustable stand, you can effortlessly adapt the monitor to your needs. Raise or lower the height, swivel left or right, or tilt the screen to reduce glare and find the optimal viewing angle. Whether you're working, designing, or attending long video calls, this flexibility helps reduce neck and back strain, improving both comfort and productivity throughout your day.

Versatile connectivity for all your devices

Connect multiple devices and accessories in one simple step with HDMI, DisplayPort and the USB hub, streamlining your workspace for maximum efficiency and ensuring a tidy, uninterrupted workflow.

SPECIFICATION

01 DISPLAY CHARACTERISTICS

Design	4-side slim bezel
Diagonal	27", 68. 5cm
Panel	IPS panel technology LED, matte finish
Native resolution	2560 x 1440 @75Hz (3.7 megapixel QHD)
Aspect ratio	16:9
Panel brightness	350 cd/m²
Static contrast	1000:1
Advanced contrast	80M:1
Response time (MPRT)	1ms
Viewing zone	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Colour support	16.7mln (sRGB: 100%; NTSC: 72%)
Horizontal Sync	30 - 112kHz
Viewable area W x H	596.7 x 335.7mm, 23.5 x 13.2"
Pixel pitch	0.233mm
Colour	matte, black

02 INTERFACES / CONNECTORS / CONTROLS

Signal input	HDMI x1 (v.1.4) DisplayPort x1 (v.1.2)
USB HUB	x2 (v. 2.0 (DC5V, 500mA))
HDCP	yes
Headphone connector	yes

03 FEATURES

Blue light reducer	yes
Flicker free	yes
Adaptive Sync support	yes
Extra	i-Style colour
OSD languages	EN, DE, FR, ES, IT, RU, JP, CZ, NL, PL, UA
Control buttons	Joystick: (Centre) Power/Menu, Up/Signal Select, Down, Left/Submenu, Right/Volume
User controls	picture adjust (brightness, contrast, ECO, ACR, OD, motion blur reduction, Adaptive Sync), colour settings (i-Style colour, blue light reducer, RGB range, colour temperature, user preset), OSD (OSD H. position, OSD V. position, OSD rotate, OSD time, OSD background, DDC/CI control, display information), language, extra1 (sharpness, video mode adjust, opening logo, power LED), extra 2 (shortcut key, FW version), input select, audio settings (volume, mute audio), reset (reset all)
Speakers	2 x 2W
Convenience	Kensington-lock™ prepared, DDC/CI, DDC2B, Mac OSX

04 MECHANICAL

Display position adjustments	height, swivel, tilt, pivot (rotation both sides)
Height adjustment	150mm
Rotation (PIVOT function)	90°
Swivel stand	360°; 180° left; 180° right
Tilt angle	23° up; 5° down
VESA mounting	100 x 100mm
Cable management system	yes

05 ACCESSORIES INCLUDED

Cables	power (1.5m), USB (1.5m), HDMI (1.5m), DP (1.8m)
Other	quick start guide, safety guide

06 POWER MANAGEMENT

Power supply unit	internal
Power supply	AC 100 - 240V, 50/60Hz
Power usage	17W default, 0.5W stand by, 0.3W off mode

07 SUSTAINABILITY

Regulations	TCO Certified, CE, TÜV-GS, EAC, VCCI-B, PSE, RoHS support, ErP, WEEE, REACH, UKCA
Energy efficiency class (Regulation (EU) 2017/1369)	D
EPEAT Silver	*registration varies by country, go to www.epeat.net for details
REACH SVHC	above 0.1%: Lead, Lead monoxide, Diboron trioxide

08 DIMENSIONS / WEIGHT

Product dimensions W x H x D	613 x 404 (548) x 224.5mm
Box dimensions W x H x D	691 x 442 x 142mm
Weight (without box)	5.7kg
Weight (with box)	8.1kg
EAN code	4948570126781

GALLERY

iiyama
ProLite
XB2793QSU
27"
IPS
68.6cm
2560x1440
SLIM BEZEL
15cm
2x2W

iiyama
ProLite
XB2793QSU
27"
IPS
68.6cm
2560x1440
SLIM BEZEL
15cm
2x2W

iiyama
ProLite
XB2793QSU
27"
IPS
2560x1440
SLIM BEZEL
15cm
2x2W

iiyama
ProLite
XB2793QSU
27"
IPS

iiyama
ProLite
XB2793QSU
27"
IPS
68.6cm
2560x1440
SLIM BEZEL
15cm
2x2W

iiyama
ProLite
XB2793QSU
27"
IPS
68.6cm
2560x1440
SLIM BEZEL
15cm
2x2W

iiyama

ProLite
XB2793QSU



27"
IPS
68.6cm
2560x1440

15cm
2x2W

iiyama

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects. **© IIYAMA CORPORATION. ALL RIGHTS RESERVED**